QUOVADIS ROOT CA2
CERTIFICATE POLICY/CERTIFICATION PRACTICE STATEMENT

OID: 1.3.6.1.4.1.8024.0.2
Effective Date: August 5,

8.4. Topics Covered By Assessment 22
8.5. Actions Taken As A Result Of Deficiency 22
8.6. Publication Of Audit Results 22
8.7 Self Audits 22

1. INTRODUCTION

1.1. Overview

QuoVadis SSL Certificates are issued for use with the SSL /TLS protocol to enable secure transactions of data through privacy, authentication, and data integrity.

QuoVadis Code Signing Certificates are used to provide users with reasonable assurance that the executable code

requests; issuing, revoking and renewing a Certificate; and the maintenance, issuance, and publication of CRLs for users within the QuoVadis PKI. In its capacity as a CA, QuoVadis will:

- Conform its operations to this CP/CPS (or other relevant business practices);
- Issue and publish Certificates in a timely manner;
- Perform verification of Certificate Holder information in accordance with this CP/CPS;
- Revoke Certificates upon receipt of a valid request from an authorised person or on its own initiative when circumstances warrant; and
- Notify Certificate Holders of the imminent expiry of their Certificates.

Issuing CAs chaining to a QuoVadis Root must not be used for Man in the Middle (MITM) purposes or for the traffic management of domain names or IP addresses that the entity does not own or control. QuoVadis will not issue a subordinate Issuing CA Certificate to be used for these purposes.

Issuing CAs chaining to a publicly trusted QuoVadis Root must either be technically constrained, or undergo an independent audit and be publicly disclosed in the Repository on the QuoVadis website (https://www.quovadisglobal.com/repository).

1.3.2. Registration Authorities

QuoVadis acts as Registration Authority (RA) for Certificates it issues. An RA is an entity that performs verification of Certificate Holder information in accordance with this CP/CPS, and revokes Certificates upon ificont oo 5( )-179(v)5(a)5(li)6 requef

1.4 Certificate Usage

1.4.1. Appropriate Certificate Uses

Certificates issued pursuant to this CP/CPS may be used for all legal authentication, encryption, access control, and digital signature purposes, as designated by the key usage and extended key usage fields found within the Certificate.

1.4.2. Prohibited Certificate Usage

QuoVadis Certificates may not be used and no participation is permitted in the QuoVadis PKI (i) in circumstances that

Certificate Holder Agreement: Is the agreement executed between a Certificate Holder and QuoVadis relating to the provision of designated Certificate-related services that governs their use of and reliance on the Certificate and Key Pair associated with the Certificate.

Certificate Requester: A Certificate Requester is a natural person who is employed by the Applicant, or an authorised agent who has express authority to represent the Applicant or a third party (such as an ISP or hosting company), and who completes and submits a Certificate Request on behalf of the Applicant.

Confirming Person: A confirming Person is a natural person who must be a senior officer of the Applicant (e.g., Secretary, President, CEO, CFO, COO, CIO, CSO, Director, etc.) who has express authority to sign the QV Authority Letter on behalf of the Applicant.

Contract Signer: A Contract Signer is a natural person who is employed by the Applicant and who has express authority to sign Certificate Holder Agreements on behalf of the Applicant.

Effective Date: Is the date that the Baseline Requirements v1.0 come into force, which is 1 July 2012.

Internal Server Name: A Server Name (which may or may not include an Unregistered Domain Name) that is not resolvable using the public DNS.

Participants: A Participant is an individual or entity within the QuoVadis PKI and may include: CAs and their Subsidiaries and Holding Companies; Certificate Holders including Applicants; and Relying Parties.

Relying Party: The Relying Party is an individual or entity that relies upon the information contained within the Certificate.

Relying Party Agreement: The Relying Party Agreement is an agreement which must be read and accepted by a Relying Party prior to validating, relying on or using a Certificate or accessing or using the QuoVadis Repository.

Repository: The Repository refers to the CRL, OCSP, and other directory services provided by QuoVadis containing issued and revoked Certificates.

Reserved IP Address: An IPv4 or IPv6 address that the IANA has marked as reserved:
http://www.iana.org/assignments/ipv4-address-space/ipv4-address-space.xml
http://www.iana.org/assignments/ipv6-address-space/ipv6-address-space.xml

2. PUBLICATION AND REPOSITORY RESPONSIBILITIES

2.1. Repositories

The QuoVadis Repository serves as the primary repository for revocation data on issued Certificates. However,

QuoVadis to verify a previously issued F H U W L I L F D W H D Q G W K D W W K H U H K D V Q R W E H H Q P R G L I L H G
V L Q F H W K H S U H Y L R X V F H U W L I L F D W H ¶ V L V V X D Q F H

3.1.8. High Risk Domains

QuoVadis maintains a list of High Risk Domains and has implemented technical controls to prevent the issuance of Certificates to certain domains. QuoVadis follows documented procedures that identify and require additional Y H U L I L F D W L R Q D F W L Y L W \ I R U + L J K 5 L V N & H U W L I L F D W H 5 H T X H V W V S U L R U W R W

3.2. Initial Identity Validation

3.2.1. Method To Prove Possession Of Private Key

The Applicant must submit a digitally signed PKCS#10 Certificate Signing Request (CSR) to establish that it holds the private key corresponding to the public key to be included in a Certificate. QuoVadis parses the PKCS#10 CSR V X E P L W W H G E \ W K H $ S S O L F D Q W L Q D V H F X U H P D Q Q H U D Q G Y H U L I L H V W K D W W K created by the private key corresponding to the public key in the PKCS#10 CSR. If any doubt exists, QuoVadis will not perform certification of the key.

3.2.2. Authentication Of Organisation Identity

4.2.2. Approval Or Rejection Of Certificate Applications

From time to time, QuoVadis may modify the requirements related to application information requested, based on QuoVadis requirements, business context of the usage of Certificates, or as may be required by law, changes to the EV Guidelines or changes to the Baseline Requirements for the Issuance and Management of Publicly-Trusted Certificates.

QuoVadis assumes that all user software will be compliant with X.509, the SSL/TLS protocol, and other applicable

- QuoVadis is made aware that a Wildcard Certificate has been used to authenticate a fraudulently misleading subordinate Fully-Qualified Domain Name;
- QuoVadis

5.2.1. Trusted Roles

In order to ensure that one person acting alone cannot circumvent security, trusted responsibilities are shared by multiple roles and individuals. This is accomplished by creating separate roles and accounts on various components of the CA system, and each role has a limited amount of capability. This method allows a system of "checks and balances" to occur among the various roles. Oversight may be in the form of a person who is not directly involved in issuing Certificates examining system records or audit logs to ensure that other persons are acting within the realms of their responsibilities and within the stated security policy. This is accomplished by creating separate roles and accounts on the service workstation, each of which has a limited amount of capability. This method allows a system of checks and balances to occur among the various roles.

5.2.2. Number Of Persons Required Per Task

At least two people are assigned to each trusted role to ensure adequate support at all times except verifying and reviewing audit logs. Some roles are assigned to different people to ensure no conflict of interest occurs and to prevent the possibility of accidental or intentional compromise of any component of the PKI, most especially the Root CA and Issuing CA private keys.

CA key pair generation and initialisation of each CA (Root and Issuing) shall require the active participation of at least two trusted individuals in each case. Such sensitive operations also require the active participation and oversight of senior management.

5.2.3. Identification And Authentication For Each Role

3HUVRQV ILOOLQJ WUXVWHG UROHV PXVW XQGHUJR DQ DSSURSULDWH VHFXU
7UXVWHG Each individual performing any of the trusted roles shall use a Certificate stored on an approved cryptographic smart card to identify themselves to the Certificate Server and Repository.

5.2.4. Roles Requiring Separation Of Duties

Operations involving Root and Issuing CA roles are segregated between M of N employees. All operations involving maintenance of audit logs are segregated.

5.3. Personnel Controls

5.3.1. Qualifications, Experience, And Clearance Requirements

Background checks are conducted on all individuals selected to take up a trusted role in the QuoVadis PKI in accordance with a designated security screening procedure, prior to the commencement of their duties.

For purposes of mitigating the risk that one individual acting alone could compromise the integrity of the QuoVadis PKI or any Certificate issued therein, QuoVadis performs relevant background checks of individuals and defines the tasks that the individuals will be responsible to perform. QuoVadis determines the nature and extent of any EDFNJURXQG FKHFNV LQ LWV VROH GLVFUHWLRQ 7 Kations with respect to IXOO\ VW personnel controls and QuoVadis shall have no other duty or responsibility with respect to the foregoing. Without limitation, QuoVadis shall not be liable for employee conduct that is outside of their duties and for which QuoVadis has no control including, without limitation, acts of espionage, sabotage, criminal conduct, or malicious interference.

5.3.2. Background Check Procedures

Background check procedures include but are not limited to checks and confirmation of:

- Previous employment
- Professional references
- Educational qualifications
- Criminal records
- Credit/financial history and status
- Driving licenses
- Social security records

Where the above checks and confirmations cannot be obtained due to a prohibition or limitation of law or other circumstances, QuoVadis will utilise available substitute investigation techniques permitted by law that provide similar information including background checks performed by applicable government agencies.

5.4.4. Protection Of Audit Log

The relevant audit data collected is regularly analysed for any attempts to violate the integrity of any element of the QuoVadis PKI. Only certain QuoVadis Trusted Roles and auditors may view audit logs in whole. QuoVadis decides whether particular audit records need to be viewed by others in specific instances and makes those records available. cert ed

5.5.7. Procedures To Obtain And Veri

within the QuoVadis environment, including the private keys, is restricted by the use of token/smart cards and associated pass phrases. These smartcards and pass phrases are allocated among multiple members of the QuoVadis management team. Such allocation ensures that no one member of the team holds total control over any component of the system. The hardware security modules are always stored in a physically secure environment and are subject to security controls throughout their lifecycle.

6.1.2. Private Key Delivery To Certificate Holder

Certificate Holders are solely responsible for the generation of the private keys used in their Certificate Requests unless specifically agreed by QuoVadis. QuoVadis does not provide SSL key generation, escrow, recovery or backup facilities.

6.1.3. Public Key Delivery To Certificate Issuer

Upon making a Certificate Application, the Certificate Holder is solely responsible for generating an RSA key pair and submitting it to QuoVadis in the form of a PKCS#10 CSR. Certificate requests are generated using the key generation facilities available in the Certificate Holder ¶ V ZsHUver software.

6.1.4. Certification Authority Public Key To Relying Parties

QuoVadis public keys are securely delivered to software providers to serve as trust anchors in commercial browsers and operating system root stores, or may be specified in a Certificate validation or path discovery policy file. Relying Parties may also obtain QuoVadis self-signed CA Certificates containing its public key from the QuoVadis web site.

6.1.5. Key Sizes

Key lengths within the QuoVadis PKI are determined by Certificate Profiles more fully disclosed in Appendix A and Appendix B. The QuoVadis Issuing CA uses an RSA minimum key length of 2048-bit modulus. Certificate Holders may submit 2048-bit or larger keys to QuoVadis.

6.1.6. Public Key Parameters Generation And Quality Checking

The cryptographic modules used by QuoVadis have been validated to conforming to FIPS 140-2 Level-3 and provide random number generation and on-board creation of suitable key lengths for RSA public key generation.

6.1.7. Key Usage Purposes (As Per X.509 V3 Key Usage Field)

QuoVadis CA Certificates include key usage extension fields to specify the purposes for which the Certificate may be used and also to technically limit the functionality of the Certificate when used with X.509v3 compliant software. Reliance on key usage extension fields is dependent on correct software implementations of the X.509v3 standard and is outside of the control of QuoVadis. Key usages are specified in the Certificate Profiles in Appendix A and B.

6.2. Private Key Protection And Cryptographic Module Engineering Controls

6.2.1. Cryptographic Module Standards And Controls

The cryptographic modules used by the QuoVadis PKI are validated to provide FIPS 140-2 Level-3 security standards in both the generation and the maintenance in all Root and Issuing CA private keys.

6.2.2. Private Key (N Out Of M) Multi-Person Control

Subject to the requirements of the CP/CPS, the QuoVadis PKI uses trusted multi-person control for both access control and authorisation control.

6.2.3. Private Key Escrow

Private keys shall not be escrowed.

6.2.4. Private Key Backup

Issuing CA private keys are stored in an encrypted VWDWH XVLQJ DQ HQFU\SWLRQ NH\ WR FUHDWH ZUDSSHU´ DURXQG WKH Access Control Key. N-of-M control as defined in this CP/CPS. Backup copies are maintained on site and in secure, offsite storage.

6.2.5. Private Key Archive

The QuoVadis PKI does not support private key archive.

6.2.6. Private Key Transfer Into Or From A Cryptographic Module

See Section 6.2.4.

6.2.7. Private Key Storage On Cryptographic Module
See Section 6.2.4.

6.2.8. M

memorized, not written down. Activation data must never be shared. Activation data must not contain WKH XVHU¶V personal information.

6.4.3. Other Aspects Of Activation Data
No stipulation.

6.5. Computer Security Controls
QuoVadis has a formal Information Security Policy that documents the QuoVadis policies, standards and guidelines relating to information security. This Information Security Policy has been approved by management and is communicated to all employees.

Computer security technical requirements are achieved utilising a combination of hardened security modules and software, operating system security features, PKI and CA software and physical safeguards, including security Policies and Procedures that include but are not limited to:

- Access controls to CA services and PKI roles;
- Enforced separation of duties for CA Services and PKI roles;
- Identification and Authentication of personnel that fulfil roles of responsibility in the QuoVadis PKI;
- Use of cryptography for session communication and database security;
- Archive of CA history and audit data;
- Use of cryptographic smart cards and x.509 Certificates for all administrators.

6.5.1. Computer Security Rating
A version of the core Certificate Authority software used by QuoVadis has obtained the globally recognised Common Criteria EAL 4+ certification.

6.6. Life Cycle Technical Controls
All hardware and software procured for the QuoVadis PKI must be purchased in a manner that will mitigate the risk that any particular component was tampered with, such as random selection of specific components. Equipment developed for use within the QuoVadis PKI shall be developed in a controlled environment under strict change control procedures.

A continuous chain of accountability, from the location where all hardware and software that has been identified as supporting a CA within the QuoVadis PKI, must be maintained by causing it to be shipped or delivered via controlled methods. Issuing CA equipment shall not have installed applications or component software that is not part of the Issuing CA configuration. All subsequent updates to Issuing CA equipment must be purchased or developed in the same manner as the original equipment and be installed by trusted and trained personnel in a defined manner.

6.6.1. System Development Controls
Formal procedures are followed for the development and implementation of new systems. An analysis of security requirements is carried out at the design and requirements specification stage. Outsourced software development projects are closely monitored and controlled.

6.6.2. Security Management Controls
Formal procedures and controls are in place to relating to the security-related configurations of 4XR9DGAL V¶ systems.

6.6.3. Life Cycle Security Controls

continuos cha continuocha

6.7 Network Security Controls

All access to Issuing CA equipment via a network is protected by network firewalls and filtering routers. Firewalls and filtering routers used for Issuing CA equipment limits services to and from the

Serial Number
Revocation Date (see CRL entry extension for Reason Code below)
, V V X H U ¶ V 6 L J Q D W X U H

7.2.2. CRL And CRL Entry Extensions

CRL Number (monotonically increasing integer - never repeated)
Authority Key Identifier (same as Authority Key Identifier in Certificates issued by CA)
CRL Entry Extensions

9. OTHER BUSINESS AND LEGAL MATTERS
9.1. Fees
9.1.1.

any information in the EV Certificate is or becomes incorrect or inaccurate, or (b) there is any actual or suspected misuse or compromise of the Certificate Holder ¶ V 3 U L Y D W H . H \ D V V R F L D W H G Z L W K W K H 3 the Certificate; and

- Termination of Use of Certificate: An obligation and warranty to promptly cease all use of the Private Key

-

- If the private key associated with the Certificate held by the claiming party or otherwise the subject of any claim has been compromised;
- If the Certificate held by the claiming party was issued in a manner that constituted a breach of any applicable law or regulation;
- Computer hardware or software, or mathematical algorithms, are developed that tend to make public key cryptography or asymmetric cryptosystems insecure, provided that QuoVadis uses commercially reasonable practices to protect against breaches in security resulting from such hardware, software, or algorithms;
- Power failure, power interruption, or other disturbanc3(r)-25eema1diskea aower -486(p)6(o)-3(w)rmer10(d)33(b6( )-59(a)5

9.10.3. Effect Of Termination And Survival

The conditions and effect resulting from termination of this CP/CPS will be communicated via the QuoVadis website upon termination. That communication will outline the provisions that may survive termination of this CP/CPS and remain in force. The res

9.16.5. Enforcement (Waiver Of Rights)

Except where an express time frame is set forth in this CP/CPS, no delay or omission by QuoVadis to exercise any right, remedy, or power it has under this CP/CPS shall impair or be construed as a waiver of such right, remedy, or power. A waiver by QuoVadis of any breach or covenant in this CP/CPS shall not be construed to be a waiver of any other or succeeding breach or covenant. No waiver shall be effective unless it is in writing. Bilateral agreements between QuoVadis and the parties to this CP/CPS may contain additional provisions governing enforcement.

9.16.6. Force Majeure

QUOVADIS ACCEPTS NO LIABILITY FOR ANY BREACH OF WARRANTY, DELAY, OR FAILURE IN PERFORMANCE THAT RESULTS FROM EVENTS BEYOND ITS CONTROL SUCH AS ACTS OF GOD, ACTS OF WAR, ACTS OF TERRORISM, EPIDEMICS, POWER OR TELECOMMUNICATION SERVICES FAILURE, FIRE, AND OTHER NATURAL DISASTERS.

9.17. Other Provisions

No stipulation.

APPENDIX A ±Root and Issuing CA Profiles

QuoVadis Root CA2

Field	Value
Version	V3
Serial Number	Unique number 0509
Issuer Signature Algorithm	sha-1WithRSAEncryption {1 2 840 113549 1 1 5}
Issuer Distinguished Name	Unique X.500 CA DN. CN = QuoVadis Root CA 2 O =QuoVadis Limited C = BM
Validity Period	25 years expressed in UTC format NotBefore: 11/24/2006 18:27:00 NotAfter: 11/24/2031 18:23:33

Appendix B ±Certificate Holder Certificate Profiles

Business SSL

Field	Value
Version	V3
Serial Number	Unique number
Issuer Signature Algorithm	sha-1WithRSAEncryption (1.2.840.113549.1.1.5) or sha256RSA (1.2.840.113549.1.1.11)
Issuer Distinguished Name	Unique X.500 CA DN. CN = QuoVadis Global SSL ICA or CN = QuoVadis Global SSL ICA G2 or CN = QuoVadis Global SSL ICA G3 O = QuoVadis Limited C = BM
Validity Period	1, 2, or 3 years expressed in UTC format
Subject Distinguished Name	
Organization Name	subject:organisationName (2.5.4.10)
Organisation Unit	subject:organisationUnit (2.5.6.5) Information not verified.
Common Name	subject:commonName (2.5.4.3) cn = Common name
State or province (if any)	subject:stateOrProvinceName (2.5.4.8)
Country	subject:countryName (2.5.4.6)
Subject Public Key Information	2048-bit RSA key modulus, rsaEncryption (1.2.840.113549.1.1.1)
Signature Algorithm	sha-1WithRSAEncryption (1.2.840.113549.1.1.5) or sha256RSA (1.2.840.113549.1.1.11)
Extension	Value
Authority Key Identifier	c=no; Octet String ±Same as Issuer's Subject Key Identifier
Subject Key Identifier	c=no; Octet String ±Same as calculated by CA from PKCS#10
Key Usage	c=yes; Digital Signature, Key Encipherment (a0)
Extended Key Usage	c=no; Server Authentication (1.3.6.1.5.5.7.3.1) Client Authentication (1.3.6.1.5.5.7.3.2)

QuoVadis may accept at its discretion other official documentation supporting an application. QuoVadis may also use the services of a third party to confirm Applicant information. QuoVadis accepts confirmation from third party organisations, other third party databases, and government entities.

Application Process
During the Certificate approval process, QuoVadis Validation Specialists employ controls to validate the identity of the Applicant and other information featured in the Certificate Application to ensure compliance with this CP/CPS.

Step 1: The Applicant provides a signed Certificate Application to QuoVadis, which includes identifying information to assist QuoVadis in processing the request and issuing the Business SSL Certificate, along with a PKCS#10 CSR and billing details.

Step 2: QuoVadis independently verifies information using a variety of sources.

Step 3: The Applicant accepts the Certificate Holder Agreement and approves Certificate issuance.

Step 4: All signatures are verified through follow-up procedures or telephone calls.

Step 5: QuoVadis obtains and documents further explanation or clarification as necessary to resolve discrepancies or details requiring further explanation. If satisfactory explanation and/or additional documentation are not received within a reasonable time, QuoVadis will decline the Certificate Request and notify the Applicant accordingly. Two QuoVadis Validation Specialists must approve issuance of the Certificate.

Step 6: QuoVadis creates the Business SSL Certificate.

Step 7: The Business SSL Certificate is delivered to the Applicant.

Renewal
Renewal requirements and procedures include verification that the Applicant continues to have authority to use the domain name, and that the Certificate Application is approved by an authorised representative of the Applicant.

Extended Validation SSL

Field	Value	Comments
Version	V3 (2)	
Serial Number	Unique number	
Issuer Signature Algorithm	sha-1WithRSAEncryption (1.2.840.113549.1.1.5) or sha256RSA (1.2.840.113549.1.1.11)	
Issuer Distinguished Name	Unique X.500 CA DN. CN = QuoVadis Global SSL ICA or CN = QuoVadis Global SSL ICA G2 or CN = QuoVadis Global SSL ICA G3 O = QuoVadis Limited C = BM	
Validity Period	1 or 2 years expressed in UTC format	
Subject Distinguished Name		
Organization Name	subject:organisationName (2.5.4.10)	7KLV ILHOG 0867 FRQWD full legal organisation name as listed in the official records of the Incorporating or Registration $JHQF\ LQ WKH Jurisdiction of Incorporation. In addition, an assumed name or d/b/a name used by the Subject MAY be included at the beginning of this field, provided that it is followed by the full le369.9T.27 Tm0 -10(t)7(i)-10(s)6( )6(fo

Subject Key Identifier	c=no; Octet String ±Same as calculated by CA from PKCS#10	
Key Usage	c=yes; Digital Signature, Key Encipherment (a0)	
Extended Key Usage	c=no; Server Authentication (1.3.6.1.5.5.7.3.1) Client Authentication (1.3.6.1.5.5.7.3.2)	
Certificate Policies	c=no; Certificate Policies; {1.3.6.1.4.1.8024.0.2.100.1.2 } [1,1] Policy Qualifier Info: Policy Qualifier Id=CPS Qualifier: http://www.quovadisglobal.com/repository [1,2] Policy Qualifier Info: Policy Qualifier Id=User Notice Qualifier: Notice Text= Any use of this Certificate constitutes acceptance of the QuoVadis Root CA 2 Certification Policies and Certificate Practice Statement.	
Subject Alternative Name	c=no; DNS = FQDN of Device (e.g., domain.com)	
Authority Information Access	c=no; Access Method= - Id-ad-ocsp (On-line Certificate Status Protocol - 1.3.6.1.5.5.7.48.1); URL =http://ocsp.quovadisglobal.com	
CRL Distribution Points	c = no; CRL HTTP URL =http://crl.quovadisglobal.com/QVSSLICA.crl or http://crl.quovadisglobal.com/qvsslg2.crl or http://crl.quovadisglobal.com/qvsslg3.crl	

Purpose of EV SSL

EV SSL Certificates are intended for use in establishing web-based data communication conduits via TLS/ 1 72.024 3589.98 41

ii. Verify Applicant (or a corporate parent/subsidiary) is a registered holder or has exclusive control of the domain name to be included in the EV Certificate;

iii. 9HULI\ $SSOLFDQW¶V DXWKRUL]DWLRQ IRU WKH (9 &HUWLILFDWH LQFOXGLQ
- Verify the name, title, and authority of the Contract Signer, Certificate Approver, and Certificate Requester;
- Verify that Contract Signer signed the Certificate Holder Agreement; and
- Verify that a Certificate Approver has signed or otherwise approved the EV Certificate Request.

The vetting regime of the EV Guidelines includes detailed verification procedures, which vary by Certificate Holder, and may include direct confirmation with Incorporating Agencies as well as correlation of information from certain qualified commercial data providers, site visits, and independent confirmations from senior officers of the Applicant. Verified opinion letters from attorneys and accountants representing the Applicant, as well as bank account verifications, may also be used to fulfil aspects of the vetting process.

Applicant Contacts
The EV Guidelines specify a number of Applicant roles involved in the EV verification process. All must be filled by

- Use of EV Certificate: An obligation and warranty to install the EV Certificate only on the server accessible at a domain name listed on the EV Certificate, and to use the EV Certificate solely in compliance with all applicable laws, solely for authorised company business, and solely in accordance with the Certificate Holder Agreement;

- Reporting and Revocation Upon Compromise: An obligation and warranty to promptly cease using an EV Certificate and its associated Private Key, and promptly request the QuoVadis to revoke the EV Certificate, in the event that: (a) any information in the EV Certificate is or becomes incorrect or inaccurate, or (b) there is any actual or suspected misuse or compromise of the Certificate Holder ¶V 3ULYDWH .H\ DVVRFLDWHG ZLWK V listed in the EV Certificate; and

- Termination of Use of EV Certificate: An obligation and warranty to promptly cease all use of the Private Key corresponding to the Public Key listed in an EV Certificate upon expiration or revocation of that EV Certificate.

Application Process

During the Certificate approval process, QuoVadis Validation Specialists employ controls to validate the identity of the Certificate Holder and other information featured in the Certificate Application to ensure compliance with the Guidelines.

Step 1: The Certificate Requester provides a signed Certificate Application to QuoVadis, which includes information about the Applicant, personnel within the organisation who have authority to approve the request and also agreement to the Certificate Holder Agreement. In addition, the Certificate Requester provides a PKCS#10 CSR as well as

In the case of outdated information, QuoVadis repeats the verification processes required by the EV Guidelines. If a company is no longer in good standing, or if any of the other required information cannot be verified, the Certificate is not renewed.

3. Obtains a biometric associated with the Subject, such as a fingerprint or notarized handwritten Declaration of Identity,
4. 9HULILHV WKH &HUWLILFDWH 5HTXHVWHU¶V DXWKRULW\ WR UHTXHVW D F request using a verified method of communication.

A Declaration of Identity is a written document that consists of the following:

1. the identity of the person performing the verification,
2.