Certification Practice Statement for PKIoverheid Certificates

Effective Date: March 22, 2021
Version: 1.6

QuoVadis Trustlink B.V.
Nevelgaarde 56
3436 ZZ Nieuwegein, The

6.1.3. Public Key Delivery To Certificate Issuer 39
6.1.4. CA Public Key To Relying Parties 39
6.1.5. Key Sizes 39
6.1.6. Public Key Parameters Generation And Quality Checking 40
6.1.7. Key Usage Purposes (As Per X.509 V3 Key Usage Field) 40
6.2. Private Key Protection And Cryptographic Module Engineering Controls 40
6.2.1. Cryptographic Module Standards And Controls 40
6.2.2. Private Key (N of M) Multi-Person Control 40
6.2.3. Private Key Escrow 40
6.2.4. Private Key Backup 40
6.2.5. Private Key Archive 40
6.2.6. Private Key Transfer Into Or From A Cryptographic Module 40
6.2.7. Private Key Storage On Cryptographic Module 41
6.2.8. Method Of Activating Private Key 41
6.2.9. Method Of Deactivating Private Key 41
6.2.10. Method Of Destroying Private Key 41
6.2.11. Cryptographic Module Rating 41
6.3. Other Aspects Of Key Pair Management 41
6.3.1. Public Key Archival 41
6.3.2. Certificate Operational Periods And Key Pair Usage Periods 41
6.4. Activation Data 42
6.4.1. Activation Data Generation And Installation 42
6.4.2. Activation Data Protection 42
6.4.3. Other Aspects Of Activation Data 43
6.5. Computer Security Controls 43
6.5.1. Specific Computer Security Technical Requirements 43
6.5.2. Computer Security Rating 43
6.6. Life Cycle Technical Controls 43
6.6.1. System Development Controls 43
6.6.2. Security Management Controls 44
6.6.3. Life Cycle Security Controls 44
6.7. Network Security Controls 44
6.8. Time-Stamping 44
7. CERTIFICATE, CRL, AND OCSP PROFILES 44
7.1. Certificate Profile 44
7.1.1. Version Numbers 45
7.1.2. Certificate Extensions 45
7.1.3. Algorithm Object Identifiers 45
7.1.4. Name Forms 45
7.1.5. Name Constraints 45
7.1.6. Certificate Policy Object Identifier 45
7.1.7. Usage Of Policy Constraints Extension 45
7.1.8. Policy Qualifiers Syntax And Semantics 45
7.1.9. Processing Semantics For The Critical Certificate Policies Extension 45
7.2. CRL Profile 45
7.2.1. Version Number 46
7.2.2. CRL And CRL Entry Extensions 46
7.3. Online Certificate Status Protocol Profile 46
7.3.1. OCSP Version Numbers 46
7.3.2. OCSP Extensions 46
8. COMPLIANCE AUDIT AND OTHER ASSESSMENTS 47
8.1. Frequency, Circumstance And Standards Of Assessment 47
8.2. Identity And Qualifications Of Assessor 48
8.3. Assessor's Relationship To Assessed Entity 48
8.4. Topics Covered By Assessment 49
8.5. Actions Taken As A Result Of Deficiency 49

9.16.2. Assignment 58
9.16.3. Severability 58
9.16.4. Enforcement (Waiver Of Rights) 58
9.16.5. Force Majeure 59
9.17. Other Provisions 59
APPENDIX A – Certificate Profiles for PKIoverheid 60
QuoVadis PKIoverheid Organisatie Persoon CA – G3 60
QuoVadis PKIoverheid Organisation Services CA – G3 62
QuoVadis PKIoverheid Burger CA – 2021 65
QuoVadis PKIoverheid Organisatie Server CA – G3 67
QuoVadis PKIoverheid Private Services CA – G1 69
QuoVadis PKIoverheid Private Personen CA – G1 72

1. INTRODUCTION

This document is the DigiCert + QuoVadis Certification Practice Statement (CPS) for PKIoverheid Certificates. QuoVadis Trustlink B.V., a subsidiary of DigiCert Inc., is a Company registered in the Netherlands, trading under the names DigiCert + QuoVadis. QuoVadis is a leading international provider of Certificates. QuoVadis was founded in 1999 and has offices in the Netherlands, Germany, Switzerland, the United Kingdom, and Bermuda. QuoVadis Trustlink B.V. is certified as a Trust Service Provider ("TSP") for the issuance of Certificates KingdTw 66.1 (r)]TR-0.0(,)oo0 Td ( )Tj -0.00(0 Td 2223T)-11.4 Td (is)Tj 021730 Td [(T)-13.EMC /H2 <</

Root CA: Staat der Nederlanden Private Root CA- G1 Domain CA: Staat der Nederlanden Private Personen CA– G1



Field	Description	Max. length
O - OrganisationName	Nameof the Organisation	64
C -		

Certificate

xi) BR Section 3.2.2.4.11 is no longer used because it is deprecated as of February 5, 2018;

xii) Confirming that the Applicant is the Domain Contact for the Base Domain Name (provided that the CA or RA is also the Domain Name Registrar or an Affiliate of the Registrar), performed in accordance with BR Section 3.2.2.4.12;

xiii) Confirming the Applicant's control over the FQDN by sending a Random Value via email to a DNS CAA

3.2.2.5. Authentication for an IP Address

For each IP Address listed in a Certificate, QuoVadis confirms that, as of the date the Certificate was issued, the Applicant controlled the IP Address by:

i) Having the Applicant demonstrate practical control over the IP Address by confirming the presence of a RequestToken or RandomValue contained in the content of a file or webpage in the form of a meta tag under the "/.well- known/pki -validation" directory on the IP Address, performed in accordance with BR Section 3.2.2.5.1;

ii) Confirming the Applicant's control over the IP Address by sending a RandomValue via email, fax, SMS, or postal mail and then receiving a confirming response utilising the RandomValue, performed in accordance with BR Section 3.2.2.5.2;

iii) Performing a reverse-IP address lookup and then verifyd (iTd s (iT229t[(R)-9.5 (a)-10 (nd)-3.2 (o)-15.2TJ 0 Tc 0 Tw 1

3.2.3.1. Natural Person

The following checksare carried out for a natural person;

i) PersonalDetails: The personal details are verified using the details on a LegalIdentity Document. This includes full legal name(s) and date of birth.

ii) Email address:Verification of the Applicant's control over the email addressis carried out by ov

3.3. IDENTIFICATION AND AUTHENTICATION FOR RE-KEY REQUESTS

3.3.1. Identification And Authentication For Routine Re-Key

Subscribers may request re-key of a Certificate prior to a Certificate's expiration.

When replacing a personal certificate at the end of its lifetime the Qualified signature of the non-repudiation (signing) Certificate can be used during registration and identification, instead of the physical presence of the certificate holder. This is subject to conditions of PKIoverheid:

- The non-repudiation certificate must be valid at the time of renewal;
- The file must be current and complete, including a copy of a valid ID document;
- Subject details in the valid non-repudiation Certificate e.g., organisation field;
- The single renewal of the certificate without physical appearance is only possible if QuoVadis issued the previous non-repudiation Certificate based on physical appearance.

After receiving a request for re-key, QuoVadis creates a new Certificate with the same Certificate contents except for a new Public Key and, optionally, an extended validity period. If the Certificate has an extended validity period, QuoVadis may perform some revalidation of the Applicant but may also rely on information previously provided or obtained. QuoVadis does not re-key a Certificate without additional Identification and Authentication if doing so would allow the Subscriber to use the Certificate beyond the limits specified for the applicable Certificate or ried

QuoVadismaintain an internal databaseof all previously revoked Certificatesand previously rejected certificate requestsdue to suspectedphishing or other frauduleer

QuoVadisdocumentspotential issuancesthat were prevented by a CAA

4.6.3.

4.8. CERTIFICATE MODIFICATION

4.8.1. Circumstances For Certificate Modification

QuoVadisdoesnot provide Certificate Modification. QuoVadismay reissueor replacea valid Certificate when the Subscriber'scommon name,organisation name,devicename,or geographict014 c

4.9.3. Procedure For Revocation Request

Subscribers may also revoke their Certificates directly via the QuoVadis Portal. QuoVadis maintains a continuous 24x7 ability to internally respond to high priority revocation requests (*see* Section 1.5.2 for contact details).

QuoVadis processes a revocation request as follows:

i) QuoVadis logs the request or problem report and the reason for requesting revocation based on the list in section 4.9.1, including contact information for the requestor. QuoVadis may also include its own reasons for revocation in the log.

ii) QuoVadis may request confirmation of the revocation from a known administrator, where applicable, via out-of-band communication (e.g., telephone, fax, etc.).

iii) If the request is authenticated as originating from the Subscriber or an authorized party, QuoVadis revokes the Certificate.

iv) For requests from third parties, QuoVadis personnel begin investigating the request within 24 hours after receipt and decide whether revocation is appropriate.

v) If QuoVadis determines that revocation is appropriate, QuoVadis personnel revoke the Certificate and update the Certificate Status including the RFC 5280 Revocation reason. If QuoVadis deems appropriate, QuoVadis may forward the revocation reports to law enforcement.

In the case of system defects, service activities, or other factors that are beyond the scope of QuoVadis, QuoVadis will do everything possible to ensure that the unavailability of the revocation facility

Before revoking an Issuing CA Certificate a last CRL is generated with a nextUpdate field value of "99991231235959Z". The last CRL is available in accordance with Section 5.5.2. QuoVadis does not issue a last CRL until all Certificates in the scope of the CRL are either expired or revoked.

After the expiry date of an Issuing CA the most recent CRL will be published for at least 1 month. QuoVadis does not use the ExpiredCertsOnCRL extension.

4.9.8. Maximum Latency For CRL

CRLs for Certificates issued to end entity Subscribers are posted automatically to the online Repository within a commercially reasonable time after generation, usually within 10 minutes of generation. Regularly scheduled CRLs are posted prior to the nextUpdate field in the previously issued CRL of the same scope.

4.9.9. On-Line Revocation/084 0 5 (/084.25[.72 (a)-7 s4oP)-4Tc 0Tw -38(me)]TJ1t6.8 (op)0.TT2 1

4.9.13. Circumstances For Suspension

No suspension of Certificates is permissible within the QuoVadis PKIo.

4.9.14. Who Can Request Suspension

No suspension of Certificates is permissible within the QuoVadis PKIo.

4.9.15. Procedure For Suspension Request

No suspension of Certificates is permissible within the QuoVadis PKIo.

4.9.16. Limits On Suspension Period

No suspension of Certificates is permissible within the QuoVadis PKIo.

4.10. CERTIFICATE STATUS SERVICES

4.10.1. Operational Characteristics

Certificate status information is available via CRL and OCSP responder. Certificates, revocation entries on a CRL or OCSP Response are not removed until after the expiration of the revoked Certificate. The serial number of a rev1 1 (i)6.941H2 <t (Ce Tc 0 Tw 1.386 0 T)-7 (il)-7.1 8n ofh1H2 <t (Cem5.8 (a 0 Tw 2.277.dp16 (2.1 e)-7 6 (

5. FACILITY, MANAGEMENT, AND OPERATIONAL CONTROLS

The section of the CPS provides a high level description of the security policy, physical and logical access control mechanisms, service levels, and personnel policies used by QuoVadis to provide trustworthy and reliable CA operations. QuoVadis maintains a security program to: i) Protect the confidentiality, integrity, and availability of data and business process; ii) Protect against anticipated threats or hazards to the confidentiality, integrity, and availability of data and business process; iii) Protect against unauthorised or unlawful access, use, disclosure, alteration, or destruction of data and business process; iv) Protect against accidental loss or destruction of, or damage to data and business processes; and v) Comply with all other security requirements applicable to the CA by law and industry best practices. QuoVadis performs an annual risk assessment to identify internal and external threats and assess likelihood and potential impact of these threats to data and business processes.

5.1. PHYSICAL CONTROLS

QuoVadis manages and implements appropriate physical security controls to restrict access to the hardware and software used in connection with CA operations.

5.1.1. Site Location and Construction

QuoVadis operations facilities are especially designed for computer operations and as such have been built to meet the security requirements that apply to QTSPs. The data centres are equipped with logical and physical controls that make QuoVadis' CA and TSA operations inaccessible to non-trusted personnel. QuoVadis operates under a security policy designed to detect, deter, and prevent unauthorised access to QuoVadis' operations.

5.1.2. Physical Access

QuoVadis allows physical access to its secure operational environment only to authorised persons. Controls have been implemented for physical access to the CA operations facilities. The physical access of persons within the secure environment is stored in a log file and periodically evaluated. Physical access to the secure environment is controlled by a combination of access passes and biometric identification.

Access to the QuoVadis Trustlink B.V. office is controlled. Access is permitted to employees with an electronic key system. Visitors to the office must be accompanied by a member of the QuoVadis staff.

5.1.3. Power And Air-Conditioning

Datacentres have primary and secondary power supplies that ensure continuous and uninterrupted access to electric power. Uninterrupted power supplies (UPS) and generators provide redundant backup power

5.1.4. Water Exposures

The cabinets housing QuoVadis' CA systems are designed to prevent and protect against water exposure

5.1.5. Fire Prevention And Protection

QuoVadis datacentres are equipped with fire suppression mechanisms

5.1.6. Media Storage

QuoVadis protects its media from accidental damage, environmental hazards, and unauthorised physical access. Backup files are created on a daily basis. QuoVadis backup files are maintained at either within the QuoVadis service operations area or in a secure off-site storage area.

5.1.7. Waste Disposal

All unnecessary copies of printed sensitive information are shredded on-site before disposal. All electronic media are physically destroyed or are overwritten multiple times to prevent the recovery of the data.

5.1.8. Off-Site Backup

An offsite location is used for the storage and retention of backup software and data. The off site storage is available to authorised personnel 24x7 for the purpose of retrieving software and data; and has appropriate levels of physical security in place (i.e. software and data are stored in fire-rated safes and containers which are located behind access-controlled doors in areas accessible only by authorised personnel).

5.2. PROCEDURAL CONTROLS

QuoVadis guarantees that physical and technical security procedure are complied with in accordance with [illegible]

- checking the correctness of the references provided by the employee;
- checking the correctness of the highest or most relevant training stated by the employee;
- requesting a Declaration of Conduct (VOG) from the employee.

5.3.3. Training Requirements

QuoVadis provides relevant skills training to all employees involved in QuoVadis' PKI and TSA operations for the personnel performing information verification duties including:

- basic PKI knowledge;
- [illegible] PKI T x x

5.4.3. Retention Period For Audit Log

QuoVadis log files for events related to Lifecycle events and Certificate lifecycle events are retained for a period of 7 years before deletion starting from the destruction of the CA Private Key or revocation or expiration of the Certificate. Log files for incidents relating to threats and risks will be retained for 18 months and then deleted.

All log files are backed up daily -0.41 .

5.5. RECORDS ARCHIVAL

5.5.1. Types Of Records Archived

QuoVadis archives documentation in accordance with its document access control policy and only makes it accessible after an authorised request.

For each Certificate, the archive contains the information related to activities concerning the creation, the issue, the use, the revocation, the period of validity and the renewal. This documentation Tw 0.217css

C 0 Tc 0 Twl.

w 3.4LBody2 0 Td (6Tj EMC /C2_0 004f 7 0 (or)c -73.001 <0078> 0 /TT5 004f 0 (5e)]TJ 0 Tc 0 /TT0 004f 7Tj 0 Tc 0 Tw ( )Tj -s)1.3 (s)[(A

5.5.6. Archive Collection System

The QuoVadis Archive Collection System is internal.

5.5.7. Procedures To Obtain And Verify Archive Information

Only CA Officers, the QuoVadis Chief Security Officer and Auditors may view the entire archive. The contents of the archives will not be released in their entirety, except when required by law or by order of a court order or other legally competent authority. QuoVadis can decide to release logs of individual transactions.

Taking into accountthe reasonfor compromise,a new CAKey Pair will be generatedto replaceend entity Certificates.

6.1.1.3. Generation of key pairs of the Subscribers

The keys of Subscribers (or data for creating Electronic Signatures) are generated within the requirements specified in EN 419 211 for QSCD's or CWA 14169 for SSCD's (transition rule eIDAS 51) "Secure signature creation devices (EAL 4+)" or equivalent security criteria.

6.1.1.4. Algorithm of key pairs of the Subscribers

With exception of the Certificate policy Private Service Server QuoVadis is not permitted with in the PKIoverheid to generate and deliver the Private Key (PKCS#12).

6.1.1.5. Key pairs managed on behalf of the Subscribers

In the case of Qualified Certificates, where QuoVadis manages the keys on behalf of the Subscriber, QuoVadis ensures:

- where the policy requires the use of a Qualified Signature Creation Device (QSCD) then the signatures are only created by the QSCD;

Signatures on CRLs, OCSP responses, and OCSP responder Certificates that provide status information for Certificates that were generated using SHA-1 may continue to be generated using the SHA-1 algorithm if it is compliant with all applicable programs listed in Section 1.1. All other signatures on CRLs, OCSP responses, and OCSP responder Certificates must use the SHA-256 hash algorithm or one that is equally or more resistant to collision attack.

6.1.6. Public Key Parameters Generation And Quality Checking

QuoVadis uses cryptographic modules that conform to FIPS 186-2 and provide random number generation and on-board generation of Public Keys and a wide range of ECC curves. The value of this public exponent equates to an odd number equal to three or more.

6.1.7. Key Usage 35 (0.Tj 0.006 Tc6..M(1Tjo(1 T(dul)6.1(4- -0ovTj -012 93.6.)]TJ 0 Tc 0 Tw 35)]74

transported between cryptographic modules, QuoVadis encrypts the Private Key and protects the keys used for encryption from disclosure. Private Keys used to encrypt backups are securely stored and require two-person access If QuoVadis becomes aware that an Issuing CA's Private Key has been communicated to an unauthorized person or an organization not affiliated with the Issuing CA, then QuoVadis will revoke all certificates that include the Public Key corresponding to the communicated Private Key.

6.2.7. Private Key Storage On Cryptographic Mo

PKIoverheid Intermediates	Valid to:	[redacted]
QuoVadisPKIoverheid EVCA *Note: This CA has been revoked.*	5-Dec-22	

7.1.1. Version Numbers

Information for interpreting Certificate and CRL Profiles may be found in IETF RFC 5280. QuoVadis Certificates for PKIoverheid follow the ITU X.509v3 standard and the PKIoverheid PvE.

For publicly-trusted TLS Certificates, QuoVadis meets the technical requirements set forth in Sections 2.2, 6.1.5, and 6.1.6 of the CA/Browser Forum Baseline Requirements and this CPS.

7.1.1.1. Serial Number

The serial number is no longer than 160 bits (20 octets) ECC Certificates. QuoVadis may select one of the following options for the Signature field in a Certificate:

- *sha256WithRSAEncryption*: 1.2.840.113549.1.1.11
- *ecdsa-with-SHA256*: 1.2.840.10045.4.3.2

QuoVadis generates non-sequential Certificate serial numbers (positive numbers greater than zero) that contain at least 64 bits of output from a CSPRNG.

7.1.2. Certificate Extensions

See Appendix A.

7.1.3. Algorithm Object Identifiers

See Appendix A.

7.1.4. Name Forms

Each Certificate includes a serial number that is unique to the Issuing CA. TLS Server Certificates cannot contain metadata and/or any other indication that the value is absent, incomplete, or not applicable. Certificates are populated with the Issuer Name and Subject Distinguished Name required under Section 3.1.1.

7.1.5. Name Constraints

All Certificates are configured to meet the applicable requirements, including Regulation (EU) No. 910/2014 , Baseline Requirements, ETSI EN 319 411-1, ETSI EN 319 411-2 and PvE (Logius,

- keyCompromise (1)
- cACompromise (2)
- affiliationChanged (3)
- superseded (4)
- cessationOfOperation (5)

7.2.1. Version Number

QuoVadisissues X.509version 2 CRLsthat contain the following fields:

Basic Contents	Value	Demarcation
Issuer.CountryName	NL	Fixed
Issuer.OrganisationName	QuoVadisTrustlink BV	Fixed
Issuer.OrgIdentifier	NTRNL-30237459	Fixed
Issuer.CommonName	Commonname of the relevant issuer	Fixed
Effective date	Date	Required
Next update	Date	Required
SignatureAlgorithm	sha256RSA	Fixed
revokedCertificates	List of revoked Certificates: x Serial Number x RevocationDate and Time x RevocationReason	Required

7.2.2. CRL And CRL Entry Extensions

QuoVadis CRLs have the following extensions:

Extension	Value
CRL Number	Never repeated monotonically increasing integer
Authority Key Identifier	Subject Key Identifier of the CRLIssuer Certificate
Invalidity Date	Optional date in UTC format
Reason Code	Reason for revocationas described in Section 7.2

7.3. ONLINE CERTIFICATESTATUSPROTOCOLPROFILE

7.3.1. OCSPVersion Numbers

OCSP Version 1, as defined by RFC 6960, is supported. OCSP Responder Certificates have a maximum validity of 12 months.

7.3.2. OCSPExtensions

The OCSPsifa0.8 (ic)-5.8 (a)-7 (te)-TJ 0 Tc 0 Tw 4.034 0 Td [

Basic Contents	Value	Demarcation
SignatureAlgorithm		

- PvEpart 3 – Generalrequirements
- PvEpart 3 – Additional requirements
- PvEpart 3a – Organisatie(G2) + OrganisatiePersoon(G3)
- PvEpart 3b – OrganisatieServices(G1 & G3)
- PvEpart 3c – CSPBurger CA(G2 & G3)
- PvEpart 3d – rtoV >>BDC i 1 2 . i a [

8.4. TOPICS COVERED BY ASSESSMENT

Audits as applicable cover QuoVadis' business practices disclosure, the integrity of QuoVadis' PKI operations, and an Issuing CAs' compliance with this CPS and referenced requirements. Audits verify that QuoVadis is compliant with the CPS and applicable standards and regulatory requirements.

8.5. ACTIONS TAKEN AS A RESULT OF DEFICIENCY

If an audit reports a material noncompliance with applicable law, this

9.4. PRIVACY OF PERSONAL INFORMATION

9.4.1. Privacy Plan

QuoVadis follows the Privacy Notices posted on its website when handling personal information. *See* https://www.quovadisglobal.com/privacy_-policy. Personal information is only disclosed when the disclosure is required by law or when requested by the subject of the personal information. Such privacy policies shall conform to applicable local privacy laws and regulations including the Council Directive 95/46/EC of the European Parliament and the Swiss Federal Act on Data Protection of June 19, 1992 (SR235.1).

9.4.2. Information Treated As Private

Personal information about (SR applicable

permission

ii) Provide accurate and complete information when communicating with QuoVadis, and respond to QuoVadis' instructions concerning Key Compromise or Certificate misuse;

iii) C

- the Relying Party has, at the time of that reliance, acted in good faith and in a manner appropriate to all the circumstances known, or circumstances that ought reasonably to have been known, to the Relying Party;
- the Relying Party has, at the time of that reliance, verified the Digital Signature, if any;
- the Relying Party has, at the time of that reliance, verified that the Digital Signature, if any, was created during the Operational Term of the Certificate being relied upon;
- the Relying Party ensures that the data signed has not been altered following signature by utilising trusted application software,
- the signature is trusted and the results of the signature are displayed correctly by utilising trusted application software;
- the identity of the Subscriber is displayed correctly by utilising trusted application software; and
- any alterations arising from security changes are identified by utilising trusted application software.

If the circumstances indicate a need for additional assurances, it is Relying Parties' responsibility to obtain such assurances. A Relying Party shall make no assumptions about information that does not appear in a Certificate. All obligations and warranties within this Section relate to Reasonable Reliance on the validity of a Digital Signature, not the accuracy of the underlying electronic record.

Any unauthorised reliance on a Certificate is at a party's own risk. Relying Party Agreements may include additional representations and warranties.

9.6.5. Representations And Warranties Of Other Participants

Participants within the QuoVadis PKI to represent and warrant that they accept and will perform any and all duties and obligations as specified by this CPS

9.7. DISCLAIMERS OF WARRANTIES

OTHER THAN AS PROVIDED IN SECTION 9.6.1, THE CERTIFICATES ARE PROVIDED "AS IS" AND "AS AVAILABLE" AND TO THE MAXIMUM EXTENT PERMITTED BY LAW, QUOVADIS DISCLAIMS ALL EXPRESS AND IMPLIED WARRANTIES, INCLUDING WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, AND NON-INFRINGEMENT. QUOVADIS DOES NOT WARRANT THAT ANY CERTIFICATE WILL MEET SUBSCRIBER'S OR ANY OTHER PARTY'S EXPECTATIONS

APPENDIX A – CERTIFICATE PROFILES FOR PKIOVERHEID

QuoVadis PKIoverheid Organisatie Persoon CA-G3

Personal Organisation Authentication G3

Basic Contents	Value	Demarcation
Subject.CommonName	CommonName	Required
name	GivenName	

Basic Contents	Value	Demarcation
Subject.OrganisationName	OrganisationName	Required
Subject.organisationalUnitName	OrganisationalUnitName	Optional / Prohibited for ProfessionCertificates
Subject.title	Title	Optional
Subject.CountryName	Country	Required
Subject.PublicKeyInfo	RSA(2048 bit)	Required
Extensions		Fixed
KeyUsage(CRITICAL)	Non-Repudiation	Fixed
extKeyUsage	DocumentSigning E-Mail Protection	Required/ optional
CertPolicyID	2.16.528.1.1003.1.2.5.2 0.4.0.19431.1.1.3eu-remote-qscd' EUSCPEUSSASCPolicy (ETSITS119 431-1)	Fixed Only included when QuoVadis generates& managesPrivate Keys on behalf of Subscriberon a QSCD
subjectAltName.Rfc822Name	Rfc822email address	Optional - for e-mail signing
subjectAltName.UserPrinciple Name(MSUPN)	MSUPNin the format: .<unique identifier>@2.16.528.1.1003.1.3.5.2.1	Required
CRLDistributionPoints	http://crl.quovadisglobal.com/pkiopersong3.crl	Fixed
AuthorityInfoAccess	http://uw.ocsp.quovadisglobal.com http://trust.quovadisglobal.com/pkiopersong3.crt	Fixed
QCStatements	Id-etsi-qcs-QcCompliance { id-etsi-qcs1 } 0.4.0.1862.1.1 Id-etsi-qct-eseal { id-etsi-qct-esign} 0.4.0.1862.1.6.1 Id-etsi-qcs-QcSSCD { id-etsi-qcs4 } 0.4.0.1862.1.4 Id-etsi-qcs-QcPDS { id-etsi-qcs5 } 0.4.0.1862.1.5	Fixed

Personal Organisation Encryption G3

Basic Contents	Value	Demarcation
	CommonName	

Basic Contents	Value	Demarcation
Subject.organisationalUnitName	OrganisationalUnitName	Optional / Prohibited for ProfessionCertificates
Subject.title	Title	Optional
Subject.CountryName	Country	Required
Subject.PublicKeyInfo	RSA(2048 bit)	Required
Extensions		Fixed
KeyUsage(CRITICAL)		

CertificatePolicies	2.16.528.1.1003.1.2.5.7 Policy Identifier=0.4.0.19431.1.1.3 ‘eu-remote-qscd’ EUSCP EUSSASC Policy (ETSITS119 431-1)

	E-Mail Protection	
CertificatePolicies	2.16.528.1.1003.1.2.3.1	Fixed
subjectAltName.Rfc822Name		

	{ id-etsi-qct-esign} 0.4.0.1862.1.6.1 Id-etsi-qcs-QcSSCD { id-etsi-qcs 4 } 0.4.0.1862.1.4 Id-etsi-qcs-QcPDS { id-etsi-qcs 5 } 0.4.0.1862.1.5	

Personal Citizen Encryption G3

Basic Contents	Value	Demarcation
Subject.commonName		

Basic Contents	Value	Demarcation
Subject.stateOrProvinceName	Stateor province	Required
Subject.localityName	City	Required
Subject.CountryName	Country	Required
Subject.PublicKeyInfo	RSA(2048 bit)	Required

Basic Contents	Value	Demarcation
	server/service. Internal domain name allowed.	
Subject.SerialNumber	SerialNumber	Required
Subject.OrganisationName	OrganisationName	Required
ationalUnitName		

Basic Contents	Value	Demarcation
	E-Mail Protection	
CertificatePolicies	2.16.528.1.1003.1.2.8.5	Fixed
subjectAltName.Rfc822Name	Rfc822email address	Optional - for e-mail signing

Basic Contents	Value	Demarcation
	http://trust.quovadisglobal.com/pkio priv-6.1 0 9.-6.1 (3o Q 2319.32 719.52 0.48 0.48 re 2.7i19.3rt6 -0 09.-6.9.-656 -0 0 9.9	

Basic Contents	Value	Demarcation
Subject.OrganisationName	OrganisationName	Required
Subject.organisationalUnitName	OrganisationalUnitName	Optional / Prohibited for ProfessionCertificates
Subject.title	Title	Optional
Subject.CountryName	Country	Required
Subject.PublicKeyInfo	RSA(2048 bit)	Required
Extensions		Fixed
KeyUsage(CRITICAL)	[redacted]	

Basic Contents	Value	Demarcation
Subject.CountryName	Country	Required
Subject.PublicKeyInfo	RSA(2048 bit)	Required

Basic Contents	Value	Demarcation
	relevant QuoVadis Certification Practice Statement and other documents in the QuoVadis repository.	