QuoVadis Root CA 2/ QuoVadis Root CA 2 G3

Certification Policy/ Certification Practice Statement



OIDs: 1.3.6.1.4.1.8024.0.2

Effective Date: March 28, 2022

Version: 2.17

TABLE OF CONTENTS

1. INTRODUCTION 1
1.1. Overview 1
1.2. Document Name And Identification

4.3.1. CA Actions During Certificate Issuance.....18.....
4.3.2. Notification To Subscriber By The CA Of Issuance Of Certificate

4.12.1. Key Archival Escrow And Recovery Policy And Practices 28
4.12.2. Session Key Encapsulation And Recovery Policy And Practices 28
5. FACILITY, MANAGEMENT, AND OPERATIONAL CONTROLS 28
5.1. Physical Controls 28
5.1.1. Site Location and Construction 28
5.1.2. Physical Access 28
5.1.3. Power And Air-Conditioning 28
5.1.4. Fire Prevention And Protection 28
5.1.5. Media Storage 29
5.1.6. Waste Disposal 29
5.1.7. Off-Site Backup 29
5.2. Procedural Controls 29
5.2.1. Trusted Roles 29
5.2.2. Number Of Persons Required Per Task 30
5.2.3. Identification And Authentication For Each Role 30
5.2.4. Roles Requiring Separation Of Duties 30
5.3. Personnel Controls 30
5.3.1. Qualifications, Experience, And Clearance Requirements 30
5.3.2. Background Check Procedures 30
5.3.3. Training Requirements 31
5.3.4. Retraining Frequency And Requirements 31
5.3.5. Job Rotation Frequency And Sequence 31
5.3.6. Sanctions For Unauthorised Actions 31
5.3.7. Independent Contractor Requirements 31
5.3.8. Documentation Supplied To Personnel 31
5.4. Audit Logging Procedures 32
5.4.1. Types Of Events Recorded 32
5.4.2. Frequency Of Processing Log 32
5.4.3. Retention Period For Audit Log 33
5.4.4. Protection Of Audit Log 33
5.4.5. Audit Log Backup Procedures 33
5.4.6. Audit Collection System 33
5.4.7. Notification To Event-Causing Subject 33
1 Tf 0 T 376.443

6.1.6. Public Key Parameters Generation And Quality Checking 37
6.1.7. Key Usage Purposes (As Per X.509 V3 Key Usage Field) 37
6.2. Private Key Protection And Cryptographic Module Engineering Controls 38
6.2.1. Cryptographic Module Standards And Controls 38
6.2.2. Private Key (N of M) Multi-Person Control 38
6.2.3. Private Key Escrow 38
6.2.4. Private Key Backup 38
6.2.5. Private Key Archive 38
6.2.6. Private Key Transfer Into Or From A Cryptographic Module 38
6.2.7. Private Key Storage On Cryptographic Module 38
6.2.8. Method Of Activating Private Key 38
6.2.9. Method Of Deactivating Private Key 39
6.2.10. Method Of Destroying Private Key 39
6.2.11. Cryptographic Module Rating 39
6.3. Other Aspects Of Key Pair Management 39
6.3.1. Public Key Archival 39
6.3.2. Certificate Operational Periods And Key Pair Usage Periods 39
6.4. Activation Data 40
6.4.1. Activation Data Generation And Installation 40
6.4.2. .....CID 78 >>BDC4m ( )Tj /TT0 1 Tf -0.005 Tc -0.08.2 492 Tm [(6.)11 (4.)11 (2.)]TJ /y2.....tio

9. OTHER BUSINESS AND LEGAL MATTERS 46
9.1. Fees 46
9.1.1. Certificate Issuance Or Renewal Fees 46
9.1.2. Certificate Access Fees 46
9.1.3. Revocation Or Status Information Access Fees 46
9.1.4. Fees For Other Services 47
9.1.5. Refund Policy 47
9.2. Financial Responsibilities 47
9.2.1. Insurance Coverage 47
9.2.2. Other Assets 47
9.2.3. Insurance Or Warranty Coverage For End-Entities 47
9.3. Confidentiality Of Business Information 47
9.3.1. Scope Of Confidential Information 47
9.3.2. Information Not Within The Scope Of Confidential Information 48
9.3.3. Responsibility To Protect Confidential Information 48
9.4. Responsibility To Protect Private Information 48
9.4.1. Privacy Plan 48
9.4.2. Information Treated As Private 48
9.4.3. Information Deemed Not Private 48
9.4.4. Responsibility To Protect Private Information 48
9.4.5. Notice And Consent To Use Private Information 48
9.4.6. Disclosure Pursuant To Judicial Or Administrative Process 49
9.4.7. Other Information Disclosure Circumstances 49
9.5. Intellectual Property Rights 49
9.5.1. Property Rights in Certificates and Revocation Information 49
9.5.2. Property Rights in the CP/CPS 49
9.5.3. Property Rights in Names 49
9.5.4. Property Rights in Keys and Key Material 49
9.5.5. Violation of Property Rights 49
9.6. Representations And Warranties 49
9.6.1. Certification Authority Representations 49
9.6.2. RA Representations and Warranties 50
9.6.3. Subscriber Representations And Warranties 50
9.6.4. Relying Parties Representations And Warranties 51
9.6.5. Representations And Warranties Of Other Participants 52
9.7. Disclaimers Of Warranties 52
9.8. Liability AND LIMITATIONS OF LIABILITY 52
9.9. Indemnities 53
9.9.1. Indemnification By QuoVadis 53
9.9.2. Indemnification By Subscribers 53
9.9.3. Indemnification By Relying Parties 53
9.10. Term And Termination 54
9.10.1. Term 54
9.10.2. Termination 54
9.10.3. Effect Of Termination And Survival 54
9.11. Individual Notices And Communications With Participants 54
9.12. Amendments

9.16.3. Severability 56
9.16.4. Enforcement (Waiver Of Rights) 57
9.16.5. Force Majeure 57
9.17. Other Provisions 57
10. APPENDIX A – ROOT CA PROFILES 58
11. APPENDIX B 60
11.1. Business SSL 60
11.2. Extended Validation SSL 63
11.3. QuoVadis Qualified Website Authentication Certificate (QCP-w) 71
11.4. QuoVadis QCP-w-psd2 75
11.5. Code Signing 78
11.6. IGTF Grid Certificates 81
11.6.1. Grid End User Certificates 81
11.6.2. Grid Server Certificates 82

maintains overall responsibility and undertakes procedures to ensure that the security and functionality of the trust service meet the appropriate requirements.

In the event of any inconsistency between this CP/CPS and the normative provisions of

External Issuing CAs chaining to a publicly trusted QuoVadis Root must either be technically constrained, or undergo an independent audit and be publicly disclosed in the QuoVadis Repository.

1.3.2. Registration Authorities

A Registration Authority (RA) is an entity that performs Identification and Authentication of Certificate Applicants, and initiates, passes along revocation requeci(g)6 (r d)6.8 (e)-19 (n)10 (nd)]TJ 0 Tc7.43Tw 1.614 0 Td ( )Tj -0.0

Contract Sig r : A Contract Signer is a natural person who is employed pplicant and who has express signSu ements on behalf of the Applic t.

Internal Se Name : A rver Name ich may or may not inclu an Un stered Domain Name) that i not resolva using the public DNS.

National Co etent Auth authority responsibl f payment rvices. The NCA approves or rejects A ris ations ayment S ce Providers in its c ntry.

Participants Particip s an individ r entity within the QuoVadis PKI a may include: CAs and their Subsidiaries d Holdi ompanies s cribers inc ding Applicants; and Re ng Par is.

Qualified Cer A Dig ificate w s prim purpose 36 (D)5.3 lu eosr (t01 Tw 1.181 tan)2 (r) .:)-2 (C)

Standards / Law	
	WebTrust for Certification Authorities – Extended ValidationSSL WebTrust for Certification Authorities – Publicly Trusted Code Signing Certificates
ETSI EN 319 401 ETSI EN 319 411	General Policy Requirements for Trust Service Providers

QuoVadis may register TLS Certificates with publicly accessible Certificate Transparency (CT) Logs. Once submitted, Certificate information cannot be removed from a CT Log.

QuoVadis' CA Certificates, CRLs and OCSP responses are regularly accessible online with systems described in Section 5.

2.2. PUBLICATION OF CERTIFICATE INFORMATION

QuoVadis publishes a Repository that lists all Certificates that have been issued or revoked. Where a Certificate including an email address is issued, the Subscriber consents for the Certificate to be published in the Repository available for Relying Parties to download. The location of the Repository and OCSP Responders are given in the individual Certificate Profiles more fully disclosed in Appendix A and Appendix B to this CP/CPS.

QuoVadis hosts test Web pages that allow Application Software Suppliers to test their software with Subscriber Certificates that chain up to each publicly trusted Root Certificate at https://chain-demos.digicert.com/.

2.3. TIME OR FREQUENCY OF PUBLICATION

QuoVadis publishes CRL and OCSP resources to allow Relying Parties to determine the validity of a QuoVadis Certificate. Certificate

https://tools.ietf.org/html/draft-ietf-acme-ip-04#Section-4, performed in accordance with BR Section 3.2.2.5.6; or

vii) Confirming the Applicant's control over the IP Address by performing the procedure documented for a "tls-alpn-01" challenge in draft 04 of "ACME IP Identifier Validation Extension," available at https://tools.ietf.org/html/draft-ietf-acme-ip-04#Section-4, performed in accordance with BR Section 3.2.2.5.7.

3.2.2.3. Wildcard Domain Validation

Before issuing a Certificate with a wildcard character (*) in a CN or subjectAltName of type DNS ID, QuoVadis programmatically enforces that the wildcard character occurs in the first label position to the left of a "registry-controlled" label or "public suffix".

3.2.2.4. Verification of Country

If the Applicant requests a publicly-trusted TLS Certificate that will contain the countryName field and other Subject Identity Information, then QuoVadis verifies the identity of the Applicant, and the authenticity of the Applicant Representative's Certificate Request using a verification process meeting the requirements of Section 3.2.2.1 in the CA/Browser Forum's Baseline Requirem TJ /Span<</MCID 3>>BDC q 1 0 0 1 [336.48 [(R)]TJ /TT2 121.2 (l133TJ 0 Tc.)]TJ 0

3.2.5. Validation Of Authority

Validation of authority is conducted in compliance with this CP/CPS and the Certificate Profiles detailed in Appendix B. Validity of authority of Applicant Representatives and Agents is verified against contractual documentation and Reliable Data Sources.

QuoVadis maintains an internal database of previously revoked Certificates and previously rejected Certificate Requests. QuoVadis uses this information to identify subsequent suspicious Certificate Requests.

4.1.2. Enrolment Process And Responsibilities

Certificate Requests must be in a form prescribed by the Issuing CA and typically include i) an application form including all registration information as described by this CP/CPS, ii) secure generation of KeyPair and delivery of the Public Key to QuoVadis (a CSR may not be required), iii) acceptance of the relevant Subscriber Agreement or other terms of use upon which the Certificate is to be issued, iv) and payment of fees. All applications are subject to review, approval, and acceptance by the Issuing CA in its discretion.

A Certificate Request may be used for multiple Certificates to be issued to the same Applicant, (subject to the updati (c)-5.8 (t h)-3.3 (e(u)-3.3)]TJdat t

4.4. CERTIFICATE ACCEPTANCE

4.4.1. Conduct Constituting Certificate Acceptance

The Certificate Requester is responsible for installing the issued Certificate on the Subscriber's computer or cryptographic module according to the Subscriber's system specifications. A Subscriber

4.6.

4.8.5. Conduct Constituting Acceptance Of A Modified Certificate

Conduct constituting acceptance of a modified Certificate is in accordance with Section 4.4.1. Modified Certificates are considered accepted 30 days after the Certificate is modified, or earlier upon use of the Certificate when evidence exists that the Subscriber used the Certificate.

4.8.6. Publication Of The Modified Certificate By The CA

QuoVadis publishes modified Certificates by delivering them to Subscribers.

4.8.7. Notification Of Certificate Modification By The CA To Other Entities

RAs may receive notification of a Certificate's modification if the RA was involved in the issuance process.

4.9. CERTIFICATE REVOCATION

ii) The Issuing CA notifies QuoVadis that the original Certificate Request was not authorised and does not retroactively grant authorisation;

iii)

iv) For requests from third parties, QuoVadis personnel begin investigating the request within 24 hours after receipt and decide whether revocation is appropriate based on the following criteria:

- the nature of the alleged problem;
- the number of reports received about a particular Certificate or website;
- the identity of the complainants (for example, complaints from a law enforcement official that a web site is engaged in illegal activities have more weight than a complaint from a consumer alleging they never received the goods they ordered); and
- relevant legislation.

v) If QuoVadis determines that revocation is appropriate, QuoVadis personnel revoke the Certificate and update the Certificate Status. If QuoVadis deems appropriate, QuoVadis may forward the revocation reports to law enforcement.

In the case of a PSD2 Certificate, the NCA identified in the Certificate may request revocation by contacting psd2@quovadisglobal.nl. NCA revocation requests are authenticated using either a previously communicated shared secret, or use of a Digital Signature supported by Qualified Certificate issued to the NCA.

QuoVadis maintains a continuous 24x7 ability to internally respond to high priority revocation requests and certificate problem reports at https://www.quovadisglobal.com/certificate -revocation and other resources listed in Section 1.5.2.1 Subscribers may also revoke their Certificates via the QuoVadis Portal.

4.9.4. Revocation Request Grace Period

Subscribers are required to request revocation within one day after detecting the loss or compromise of the Private Key.No grace<</Td [(R)1 (evo)2 (n)23(f)7.8 (i) tratievonfmt4 (at)6KKed11.9 (r)102i riRnf.8 J 0 To.2 (at)6.6 (es)2.2

4.9.6. Revocation Checking Requirement For Relying Parties

Prior to relying on information listed in a Certificate, a Relying Party must confirm the validity of each Certificate in the Certificate path in accordance with IETF PKIX standards, including checking for Certificate validity, issuer-to-subject name chaining, policy and key use constraints, and revocation status through CRLs or OCSP responders identified in each Certificate in the chain.

4.9.7. CRL Issuance Frequency

QuoVadis uses its offline Root CAs to publish CRLs for its Issuing CAs at least every 6 months and within 18 hours after revoking an Issuing CA Certificate. QuoVadis updates the CRL for end-user Certificates at least every 12.5 hours and the date of the nextUpdate field will not be more than 72.5 hours after the date in the thisUpdate field.

Before revoking an Issuing CA Certificate a last CRL is generated with a "nextUpdate" field value of "99991231235959Z". The last CRL is available in accordance with Section 5.5.2. QuoVadis does not issue a last CRL until all Certificates in the scow(r)3.37t464 0 Td [0.00Tw 0.807 0 Td [(Ta])Tj -0.00sc ia009 Tw 0 (ef)7.7 exeefefo3

5.1.5. Media Storage

QuoVadis protects its media from accidental damage, environmental hazards, unauthorised physical access, and from obsolescence/deterioration during the period that records are required to be retained. Backup files are created on a daily basis. QuoVadis backup files are maintained at either within the QuoVadis service operations area or in a secure off-site storage area.

5.1.6. Waste Disposal

All unnecessary copies of printed sensitive information are shredded on-site before disposal. All electronic media are physically destroyed or are overwritten multiple times to prevent the recovery of the data.

5.1.7. Off-Site Backup

An offsite location is used for the storage and retention of backup software and data. The off site storage is available to authorised personnel 24x7 for the purpose of retrieving software and data; and has appropriate levels of physical security in place (i.e. software and data are stored in fire-rated safes and containers which are located behind access-controlled doors in areas accessible only by authorised personnel).

5.2. PROCEDURAL CONTROLS

Administrative processes are described in detail in the various documents used within and supporting the QuoVadis PKI. Administrative procedures related to personnel and procedural requirements, as well as physical and technological security mechanisms, are maintained in accordance with this CP/CPS and other relevant operational documents. Except for certain RA functions described in this CP/CPS, QuoVadis does not outsource operations associated with Root CA2.

5.2.1. Trusted Roles

Personnel acting in trusted roles include CA, TSA, and RA system administration personnel, and personnel involved with identity vetting and the issuance and revocation of Certificates. The functions and duties performed by persons in trusted roles are distributed so that one person alone cannot circumvent security measures or subvert the security and trustworthiness of the PKI. A list of personnel appointed to trusted roles is maintained and reviewed annually.

5.2.1.6. Security Officers

The Security Officer is responsible for administering and implementing security practices.

5.2.2. Number Of Persons Required Per Task

QuoVadis requires that at least two people acting in a trusted role take action for the most sensitive tasks, such as activating QuoVadis Private Keys, generating a CA Key Pair, or backing up a QuoVadis Private Key. The Internal Auditor may serve to fulfill the requirement of multiparty control for physical access to the CA system but not logical access.

5.2.3. Identification And Authentication For Each Role

Persons filling trusted roles must undergo an appropriate security screening procedure commensurate to their role and access privileges are configured using the "least privileges" principle for the role. All personnel are required to authenticate themselves to CA, TSA, and RA systems before they are allowed access to systems necessary to perform their trusted roles.

5.2.4. Roles Requiring Separation Of Duties

Trusted roles requiring a separation of duties include those performing:

- authorisation functions such as the verification of information in Certificate Requests and certain approvals of Certificate applications and revocation requests,
- backups, recording, and record keeping functions;
- audit, review, oversight, or reconciliation functions; and
- duties related to CA/TSA key management or CA/TSA administration.

To accomplish this separation of duties, QuoVadis specifically designates individuals to the trusted roles defined in Section 5.2.1 above. Individuals designated as Registration Officer or Administrator may perform Operator duties, but an Internal Auditor may not assume any other role. QuoVadis systems identify and authenticate individuals acting in trusted roles and restrict an individual from assuming multiple roles at the same time.

5.3. PERSONNEL CONTROLS

5.3.1. Qualifications, Experience, And Clearance Requirements

The PMA is responsible and accountable for QuoVadis PKI operations and ensures compliance with this CP/CPS. Prior to the engagement of any person in the Certificate management process, QuoVadis verifies the identity and trustworthiness of such person. QuoVadis determines that all individuals assigned to trusted roles perform their prospective job responsibilities competently and satisfactorily as required.

Without limitation, QuoVadis shall not be liable for employee conduct that is outside of their duties and for which QuoVadis has no control including, without limitation, acts of espionage, sabotage, criminal conduct, or malicious interference.

5.3.2. Background Check Procedures

in local law, QuoVadis utilises a substitute investigative technique permitted by law that provides substantially similar information, including but not limited to obtaining a background check performed by the applicable governmental agency.

5.3.3. Training Requirements

QuoVadis provides relevant skills training in QuoVadis' PKI and TSA operations for the personnel performing information verification duties including:

- basic PKI knowledge;
- software versions used by QuoVadis;
- authentication and verification policies and procedures;
- QuoVadis security principles and mechanisms;
- disaster recovery and business continuity procedures;
- common threats to the validation process, including phishing and other social engineering tactics; and
- CA/Browser Forum Guidelines and other applicable industry and government guidelines.

QuoVadis maintains records of who received training. Registration Officers must have the miniminlTw 1.831 0 4;Tw 0 -168

5.4. AUDIT LOGGING PROCEDURES

5.4.1. Types Of Events Recorded

QuoVadis records details of the actions taken to process a Certificate Request and to issue a Certificate, including all information generated and documentation received in connection with the Certificate Request. QuoVadis logs the following events:

- CA Certificate and key lifecycle management events;
  - Certificate requests, renewal, and re-key requests, and revocation;
  - Approval and rejection of Certificate Requests;
  -

5.4.3. Retention Period For Audit Log

Audit logs relating to the Certificatelifecycle are retained as archivte87.8 (ec)1.o (i)6.1 (te87. (ed)6.(as)2.3f[(C)-4.o (i)6.1 (t

- Compliance auditor reports
- CP/CPS versions
- Contractual obligations and other agreements concerning the operation of the CA
- System and equipment configurations, modifications, and updates
- Certificate request and verification
- Rejection or acceptance of a Certificate Request
- Certificate issuance, rekey, renewal, and revocation requests (and related actions)
- Certificate acceptance including Subscriber Agreements
- Escrow and retrieval requests
- Audit logs
- CA Key generation and destruction
- Appointment of an individual to a trusted role
- Destruction of a cryptographic module

5.5.2. Retention Period For Archive

Audit logs relating to the certificate lifecycle are retained as archive records for a period of for seven (7) years. Detailed system generated logs are retained for 18 months based on a risk assessment.

i) notify relevant Government and Certification bodies under applicable laws and related regulations;

ii) provide notice and information about the termination by sending notice by email to its customers, Application Software Suppliers

6.1.4. CA Public Key To Relying Parties

QuoVadis' Public Keys are provided to Relying Parties as specified in a certificate validation or path discovery policy file, as trust anchors in commercial browsers and operating system root stores, and/or as roots signed by other CAs. All Accreditation Authorities supporting QuoVadis Certificates and all Application Software

6.2. PRIVATE KEY PROTECTION AND CRYPTOGRAPHIC MODULE ENGINEERING CONTROLS

6.2.1. Cryptographic Module Standards And Controls

The cryptographic modules used by the QuoVadis PKI are validated to provide FIPS 140-2 Level-

6.2.9. Method Of Deactivating Private Key

QuoVadis' Private Keys are deactivated via manual and passive logout procedures on the applicable HSM device when not in use. QuoVadis never leaves its HSM devices in an active unlocked or unattended state.

Subscribers should deactivate their Private Keys via logout and removal procedures when not in use.

6.2.10. Method Of Destroying Private Key

QuoVadis personnel, acting in trusted roles, destroy CA, RA, and status server Private Keys when no longer needed. Subscribers shall destroy their Private Keys when the corresponding Certificate is revoked or expired or if the Private Key is no longer needed.

QuoVadis may destroy a Private Key by deleting it from all known storage partitions. QuoVadis also zeroizes the HSM device and associated backup tokens according to the specifications of the hardware manufacturer. This reinitializes the device and overwrites the data with binary zeros. If the zeroization or re

6.4. ACTIVATION DATA

6.4.1. Activation Data Generation And Installation

QuoVadis activates the cryptographic module containing its CA Private Keys according to the specifications of the hardware manufacturer meeting the requirements of FIPS 140-2 Level 3 and/or Common Criteria EAL 4. The cryptographic hardware is held under two-person control as explained in Section 5.2.2 and elsewhere in this CP/CPS. QuoVadis will only transmit activation data via an appropriately protected channel and at a time and place that is distinct from the delivery of the associated cryptographic module.

QuoVadis personnel and Subscribers are instructed to use strong passwords and to protect PINs and passwords that meet the requirements specified by the CA/Browser Forum's Network Security Requirements and other relevant standards.

6.4.2. Activation Data Protection

If activation data must be transmitted, it shall be via a channel of appropriate protection, and distinct in time and place from the associated Cryptographic Module. PINs may be supplied to Users in two portions using different delivery methods, for example by e-mail and by standard post, to provide increased security against third-party interception of the PIN. Activation Data should be memorised, not written down. Activation Data must never be shared. Activation data must not consist solely of information that could be easily guessed, e.g., a Subscriber's personal information.

6.4.3. Other Aspects Of Activation Data

Where a PIN is used, the User is required to enter the PIN and identification details such as their Distinguished Name before they are able to access and install their Keys and Certificate.

6.5. COMPUTER SECURITY CONTROLS

QuoVadis has a formal Information Security Policy that documents the QuoVadis policies, standards and guidelines relating to information security. This Information Security Policy has been approved by management and is communicated to all employees.

6.5.1. Specific Computer Security Technical Requirements

QuoVadis secures its CA systems and authenticates and protects communications between its systems and trusted roles. QuoVadis' CA servers and support-and-vetting workstations run on trustworthy systems that are configured and hardened using industry best practices. All CA systems are scanned for malicious code and protected against spyware and viruses. Inactivity log out timeframes are set and enforced through internal information security policies and procedures to ensure security.

RAs must ensure that the systems maintaining RA software and data files are trustworthy systems secure from unauthorized access, which can be demonstrated by compliance with audit criteria applicable under Section 5.4.1.

QuoVadis' CA systems are configured to:

i) authenticate the identity of users before permitting access to the system or applications;
ii) manage the privileges of users and limit users to their assigned roles;
iii) generate and archive audit records for all transactions;
iv) enforce domain integrity boundaries for security critical processes; and
v) support recovery from

The QuoVadis security policy is to block all ports and protocols and open only ports necessary to enable CA functions. All CA equipment is configured with a minimum number of services and all unused network ports and services are disabled.

6.8. TIME-STAMPING

See Section 5.5.5. In addition, QuoVadis provides a Time-Stamp Authority (TSA) service for use with specific QuoVadis products such as Code Signing Certificates. The QuoVadis Time-Stamp Policy/Practice Statement is structured in accordance with ETSI EN 319 421 and should be read in conjunction with this CP/CPS.

7. CERTIFICATE, CRL, AND OCSP PROFILES

QuoVadis uses the ITU X.509, version 3 standard to construct Certificates. QuoVadis adds certain certificate extensions to the basic certificate structure for the purposes intended by X.509v3 as per Amendment 1 to ISO/IEC 9594-8, 1995. *See* Appendix A and Appendix B.

For publicly-trusted TLS Certificates, QuoVadis meets the technical requirements set forth in Sections 2.2, 6.1.5, and 6.1.6 of the CA/Browser Baseline Requirements and this CP/CPS.

QuoVadis generates non-sequential Certificate serial numbers (positive numbers greater than zero) that contain at least 64 bits of output from a CSPRNG.

7.1. CERTIFICATE PROFILE

7.1.1. Version Number(s)

All Certificates are X.509 version 3 Certificates.

7.1.2. Certificate Extensions

The extensions defined for X.509 v3 Certificates provide methods for associating additional attributes with users or Public Keys and for managing relationships between CAs. *See* Appendix A and Appendix B.

For Root CA, Subordinate CA, and Subscriber Certificates used for publicly-trusted TLS, QuoVadis abide by Section 7.1.2 of the Baseline Requirements and configure the Certificate extensions to those requirements.

For TLS Certificates, the subjectAltName extension is populated in accordance with RFC 5280 with the authenticated value in the Common Name field of the subject DN (domain name or public iPAddress). The SubjectAltName extension may contain additional authenticated domain names or public iPAddresses.

For internationalized domain names, the Common Name is represented as a punycode value and that Common Name will be represented in the Subject Alternative Name extension as a punycoded A-label value. These different encodings of the same name are treated as equal values for the purposes of Common Name to Subject Alternative Name duplication requirements.

QuoVadis' Technically Constrained Subordinate CA Certificates include an Extended Key Usage (EKU) extension specifying all extended key usages for which the Subordinate CA Certificate is authorized to issue certificates. The anyExtendedKeyUsage KeyPurposeId does not appear in the EKU extension of publicly-trusted certificates.

7.1.3. Algorithm Object Identifiers

QuoVadis Certificates are signed using one of the following algorithms or others as approved in accordance with Section 1.1:

sha256WithRSAEncryption	[iso(1) member-body(2) us(840) rsadsi(113549) pkcs(1) pkcs-1(1) 11]
sha384WithRSAEncryption	[iso(1) member-body(2) us(840) rsadsi(113549) pkcs(1) pkcs-1(1) 12]
sha512WithRSAEncryption	[iso(1) member-body(2) us(840) rsadsi(113549) pkcs(1) pkcs-1(1) sha512WithRSAEncryption(13)]
ecdsa-with-SHA256	[iso(1) member-body(2) us(840) ansi-X9-62 (10045) signatures(4) ecdsa-with-SHA2 (3) 2]

ecdsa-with-SHA384	[iso(1) member-body(2) us(840) ansi-X9-62 (10045) signatures(4) ecdsa-with-SHA2(3) 3]
id-RSASSA-PSS	[iso(1) member-body-mb- me 526 Tm4r318.T61 0 9.96 6 (1)0.8 (0) ET Q

Field	Value

- All Relying Parties who reasonably rely on a Valid Certificate; and
- All Application Software Vendors with whom QuoVadis has entered into a contract for inclusion of its Root Certificate in software distributed by such Application Software Vendor

QuoVadis discharges its obligations by:

- QuoVadis complies, in all material aspects, with this CP/CPS, and all applicable laws and regulations;
- QuoVadis publishes and updates CRLs and OCSP responses on a regular basis; bau8003 Tw03 Tw03/TT1 10.04 (i)

i) Securely generate its Private Keys and protect its Private Keys from compromise, and exercise sole and complete control and use of its Private Keys

ii) Provide accurate and complete information when communicating with QuoVadis, and to respond to

PERMITTED BY APPLICABLE LAW AND NOTWITHSTANDING ANY FAILURE OF ESSENTIAL PURPOSE OF ANY LIMITED REMEDY OR LIMITATION OF LIABILITY: (A) QUOVADIS AND ITS AFFILIATES, SUBSIDIARIES, OFFICERS, DIRECTORS, EMPLOYEES, AGENTS, PARTNERS AND LICENSORS (THE "QUOVADIS ENTITIES") WILL NOT BE LIABLE FOR ANY SPECIAL, INDIRECT, INCIDENTAL, CONSEQUENTIAL, OR PUNITIVE DAMAGES (INCLUDING ANY DAMAGES ARISING FROM LOSS OF USE, LOSS OF DATA, LOST PROFITS, BUSINESS INTERRUPTION, OR COSTS OF PROCURING SUBSTITUTE SOFTWARE OR SERVICES) ARISING OUT OF OR RELATING TO THIS CP/CPS OR THE SUBJECT MATTER HEREOF; AND (B) THE QUOVADIS ENTITIES' TOTAL CUMULATIVE LIABILITY ARISING OUT OF OR RELATING TO THIS CP/CPS OR THE SUBJECT MATTER HEREOF WILL NOT EXCEED THE AMOUNTS PAID BY OR ON BEHALF OF SUBSCRIBER TO QUOVADIS IN THE TWELVE MONTHS PRIOR TO THE EVENT GIVING RISE TO SUCH LIABILITY, REGARDLESS OF WHETHER SUCH LIABILITY ARISES FROM CONTRACT, INDEMNIFICATION, WARRANTY, TORT (INCLUDING NEGLIGENCE), STRICT LIABILITY OR OTHERWISE, AND REGARDLESS OF WHETHER QUOVADIS HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH LOSS OR DAMAGE. NO CLAIM, REGARDLESS OF FORM, WHICH IN ANY WAY ARISES OUT OF THIS CP/CPS, MAY BE MADE OR BROUGHT BY SUBSCRIBER OR SUBSCRIBER'S REPRESENTATIVES MORE THAN ONE (1) YEAR AFTER THE BASIS FOR THE CLAIM BECOMES KNOWN TO SUBSCRIBER.

For EU Qualified Certificates, QuoVadis liability is in accordance with Extract 37 and Article 13 of the eIDAS Regulation.

9.9. INDEMNITIES

9.9.1. Indemnification By QuoVadis

To the extent permitted by applicable law, QuoVadis shall indemnify each Application Software Vendor against any claim, damage, or loss suffered by an Application Software Vendor related to an Certificate issued by QuoVadis, regardless of the cause of action or legal theory involved, except where the claim, damage, or loss suffered by the Application Software Vendor was directly caused by the Application Software Vendor's software displaying either (i) a valid and trustworthy Certificate as not valid or trustworthy or (ii) displaying as trustworthy (a) an Certificate that has expired or (b) a revoked Certificate where the revocation status is available online but the Application Software Vendor's software failed to check or ignored the status.

9.9.2. Indemnification By Subscribers

To the extent permitted by law, each Subscriber shall indemnify QuoVadis, its partners, and their respective directors, officers,thy, -0 0 12 9 me (f)7.89 (o)6.8(o)

9.10. TERM AND TERMINATION

9.10.1. Term

efforts to resolve such dispute via business discussions. If the dispute is not resolved within sixty (60) days after the initial notice, then a party may proceed as permitted under applicable law and as specified under

limitation of liability, disclaimer of a warranty, or an exclusion of damages is severable and independent of any other provision.

9.16.4. Enforcement (Waiver Of Rights)

QuoVadis may seek indemnification and attorneys' fees from a party for damages, losses, and expenses related to that party's conduct. QuoVadis' failure to enforce a provision of this CP/CPS does not waive QuoVadis' right to enforce the same provision later or right to enforce any other provision of this CP/CPS. To be effective, waivers must be in writing and signed by QuoVadis.

9.16.5. Force Majeure

QuoVadis is not liable for any delay or failure to perform an obligation under this CP/CPS to the extent that the delay or failure is caused by an occurrence beyond QuoVadis' reasonable control. The operation of the Internet is beyond QuoVadis' reasonable control.

To the extent permitted by applicable law, Subscriber Agreements and Relying Party Agreements shall include a force majeure clause protecting QuoVadis.

9.17. OTHER PROVISIONS

No stipulation.

10. APPENDIX A – ROOT CA PROFILES

QuoVadis Root CA2

Field	Value
Version	V3
Serial Number	Unique number 0509
Issuer Signature Algorithm	sha-1WithRSAEncryption {1 2 840 113549 1 1 5}
Issuer Distinguished Name	Unique X.500 CA DN. CN = QuoVadis Root CA 2 O =QuoVadis Limited C = BM
Validity Period	25 years expressed in UTC format NotBefore: 11/24/2006 18:27:00 NotAfter: 11/24/2031 18:23:33
Subject Distinguished Name	CN = QuoVadis Root CA 2 O =QuoVadis Limited C = BM
Subject Public Key Information	Public Key Algorithm: Algorithm ObjectId: 1.2.840.113549.1.1.1 RSA Algorithm Parameters 05 00 Public Key Length: 4096 bit
Issuer's Signature	sha-1WithRSAEncryption {1 2 840 113549 1 1 5}
Extension	Value
Authority Key Identifier	c=no; KeyID=1a 84 62 bc 48 4c 33 25 04 d4 ee d0 f6 03 c4 19 46 d1 94 6b Certificate Issuer: Directory Address: CN=QuoVadis Root CA 2 O=QuoVadis Limited C=BM Certificate SerialNumber=05 09
Subject Key Identifier	c=no; 1a 84 62 bc 48 4c 33 25 04 d4 ee d0 f6 03 c4 19 46 d1 94 6
Key Usage	c=no; CertificateSigning, Offline CRL Signing, CRL Signing (06)
Basic Constraints	c=yes; Subject Type=CA Path Length Constraint=None
Key Id Hash(sha1):	73 97 82 ea b4 04 16 6e 25 d4 82 3c 37 db f8 a8 12 fb cf 26
Cert Hash(sha1):	ca 3a fb cf 12 40 36 4b 44 b2 16 20 88 80 48 39 19 93 7c f7

QuoVadis Root CA 2 G3

11. APPENDIXB

11.1. BUSINESS SSL

Field	Value
Version	V3
Serial Number	Unique number
Issuer Signature Algorithm	sha256RSA (1.2.840.113549.1.1.11)
Issuer Distinguished Name	Unique X.500 CA DN. CN = Variable O = QuoVadis Limited C = BM
Validity Period	397 days
Subject Distinguished Name	
Organization Name	subject:organisationName (2.5.4.10)
Organisation Unit	Not permitted in QuoVadis BusinessSSL.
Common Name	subject:commonName (2.5.4.3) cn = Common name
State or province (if any)	subject:stateOrProvinceName (2.5.4.8)
Country	subject:countryName (2.5.4.6)
Subject Public Key Information	2048-bit RSA key modulus, rsaEncryption (1.2.840.113549.1.1.1)
Signature Algorithm	sha256RSA (1.2.840.113549.1.1.11)
Extension	Value
Authority Key Identifier	c=no; Octet String – Same as Issuer's Subject Key Identifier
Subject Key Identifier	c=no; Octet String – Same as calculated by CA from PKCS#10
Key Usage	c=yes; Digital Signature, Key Encipherment (a0)
Extended Key Usage	c=no; Server Authentication (1.3.6.1.5.5.7.3.1) Client Authentication (1.3.6.1.5.5.7.3.2)
Certificate Policies	c=no; Certificate Policies{1.3.6.1.4.1.8024.0.2.100.1.1 } Certificate Policies; {2.23.140.1.2.2} [1,1] Policy Qualifier Info: Policy Qualifier Id=CPS Qualifier: http://www.quovadisglobal.com/repository

Authority Information Access	c=no; AccessMethod=Id-ad-ocsp (Online Certificate Status Protocol - 1.3.6.1.5.5.7.48.1); URL=http://ocsp.quovadisglobal.com
CRL Distribution Points	

Verification of Country: QuoVadis verifies the country associated with the Subject using one of the following:

i) the IP Address range assignment by country for either (i) the web site's IP address, as indicated by the DNS record for the web site or (ii) the Applicant's IP address;

ii) the ccTLD of the requested Domain Name;

iii) information provided by the Domain Name Registrar; or

iv) a method identified in "Identity" above.

ceName (1.3.6.1.4.1.311.60.2.1.2)	Full name of Jurisdiction of Incorporation for an Incorporating or Registration Agency at the state or province level, including country information as follows, but not city or town information above.	(1.3.6.1.4.1.311.60.2.1.2)
subject:jurisdictionOfIncorporationCountryName (1.3.6.1.4.1.311.60.2.1.3)	ASN.1- X520countryName as specified in RFC 5280 Jurisdiction of Incorporation for an Incorporating or Registration Agency at the country level would include country information but would not include state or province or city or town information. Country information MUST be specified using the applicable ISO country code.	subject:jurisdictionOfIncorporationCountryName (1.3.6.1.4.1.311.60.2.1.3)
Subject:serialNumber (2.5.4.5)	For Private Organisations and Business Entities, this field MUST contain the unique Registration Number assigned to the Subject by the Incorporating or Registration Agency in its Jurisdiction of Incorporation. If the Incorporating or Registration Agency does not provide Registration Numbers, then the field will contain the date of incorporation or registration. For Government Entities, that do not have a Registration Number or verifiable date of creation, the field will contain the label “Government Entity”.	Subject:serialNumber (2.5.4.5)
Subject:businessCategory (2.5.4.15)	This field MUST contain one of the following strings: "Private Organization", "Government Entity", "Business Entity", or "Non-Commercial Entity", depending on which Section of the EV Guidelines applies to the Subject.	Subject:businessCategory (2.5.4.15)
Number & street (optional)	subject:streetAddress (2.5.4.9)	
City or town	subject:localityName (2.5.4.7)	
State or province (if any)	subject:stateOrProvinceName (2.5.4.8)	
Country	subject:countryName (2.5.4.6)	
Postal code (optional)	subject:postalCode (2.5.4.17)	
Subject Public Key Information	2048-	

Certificate Policies; {2.23.140.1.1}

[1,1] Policy Qualifier Info:
Policy Qualifier Id=CPS

Qualifier:
http://www.quovadisglobal.com/repository

[1,2] Policy Qualifier Info:
Policy Qualifier Id=User Notice

Qualifier: Notice Text= Any use of this Certificate

- Status: QuoVadis will follow the requirements of the EV Guidelines and maintains a 24/7 online accessible Repository with current information regarding the status of the EV Certificate as Valid or Revoked; and
- Revocation: QuoVadis will follow the requirements of the EV Guidelines and revoke the EV Certificate upon the occurrence of any revocation event as specified in the EV Guidelines.

Verification Requirements

Before issuing an EV Certificate, QuoVadis ensures that all Subject organisation information in the EV Certificate conforms to the requirements of, and has been verified in accordance with, the EV Guidelines and matches the information confirmed and documented by the CA pursuant to its verification processes. Such verification processes are intended to accomplish the following:

i) Verify Applicant's existence and identity, including;

- Verify Applicant's legal existence and identity (as established with an Incorporating Agency),
- Verify Applicant's physical existence (business presence at a physical address), and
- Verify Applicant's operational existence (business activity).

ii) Verify Applicant (or a corporate parent/subsidiary) is a registered holder or has exclusive control of the domain name to be included in the EV Certificate;

iii) Verify Applicant's authorisation for the EV Certificate, including;

- Verify the name, title, and authority of the Contract Signer, Certificate Approver, and Certificate Requester;
- Verify that Contract Signer signed the Subscriber Agreement; and
- Verify that a Certificate Approver has signed or otherwise approved the EV Certificate Request.

The vetting regime of the EV Guidelines includes detailed verification procedures, which vary by Subscriber, and may include direct confirmation with Incorporating Agencies as well as correlation of information from certain qualified commercial data providers, site visits, and independent confirmations from senior officers of the Applicant. Verified opinion letters from attorneys and accountants representing the Applicant, as well as bank account verifications, may also be used to fulfil aspects of the vetting process.

Applici640(i)6.8 (7.1 (a)-7 (tion)(V)-11.5 (G)-4.5 (u)r)10.3 (e6-5.81 (n)2.8 .9 (y-)3.8 (e A>>BDC /TT2 1 Tf -0.001 Tc -0.002

- Confirming Person: Must be a senior officer of the Applicant (e.g., Secretary, President, CEO, CFO, COO, CIO, CSO, Director, etc.) able to sign the QV Authority Letter on behalf of the Applicant.

Subscriber Agreement

Each Applicant must enter into a Subscriber Agreement with QuoVadis which specifically names both the Applicant and the individual Contract Signer signing the Agreement on the Applicant's behalf, and contains provisions imposing on the Applicant the following obligations and warranties:

- Accuracy of Information: An obligation and warranty to provide accurate and complete
- [illegible]

Organisation Unit	subject:organisationUnit (2.5.6.5)	Not permitted
Common Name	subject:commonName (2.5.4.3) cn = Common name	SubjectAlternativeName:dNSName is found below in this table. This field MUST contain one or more host domain name(s) owned or controlled by the Subject and to be associated with Subject's publicly accessible server. Such server may be owned and operated by the Subject or another entity (e.g., a hosting service). Wildcard Certificates are not allowed for EV Certificates.
City or Town of Incorporation	subject:jurisdictionOfIncorporationLocalityName (1.3.6.1.4.1.311.60.2.1.1)	ASN.1- X520LocalityName as specified in RFC 5280 Full name of Jurisdiction of Incorporation for an Incorporating or Registration Agency at the city or town level, including both country and state or province information as follows.
State/ Province of Incorporation	subject:jurisdictionOfIncorporationStateOrProvinceName (1.3.6.1.4.1.311.60.2.1.2)	ASN.1- X520StateOrProvinceName as specified in RFC 5280 Full name of Jurisdiction of Incorporation for an Incorporating or Registration Agency at the state or province level, including country information as follows, but not city or town information above.
Country of Incorporation	subject:jurisdictionOfIncorporationCountryName (1.3.6.1.4.1.311.60.2.1.3)	ASN.1- X520countryName as specified in RFC 5280 Jurisdiction of Incorporation for an Incorporating or Registration Agency at the country level would include country information but would not include state or province or city or town information. Country information MUST be specified using the applicable ISO country code.
Registration Number	Subject:serialNumber (2.5.4.5)	For Private Organisations and Business Entities, this field MUST contain the unique Registration Number assigned to the Subject by the Incorporating or Registration Agency in its Jurisdiction of Incorporation. If the Incorporating or Registration Agency does not provide Registration Numbers, then the field will contain the date of incorporation or registration. For Government Entities, that do not have a Registration Number or verifiable date of creation, the field

Certificate Transparency (optional)	(1.3.6.1.4.1.11129.2.4.4) This field MAY include two or more Certificate Transparency proofs from approved CT Logs.	
Subject Alternative Name	c=no; DNS = FQDN of Device (e.g., domain.com)	
Authority Information Access	c=no; Access Method= Id-ad-ocsp (On-line Certificate Status Protocol - 1.3.6.1.5.5.7.48.1); URL =http://ocsp.quovadisglobal.com Access Method=Certification Authority Issuer (1.3.6.1.5.5.7.48.2); URL = http://trust.quovadisglobal.com/qvq_webg1.crt	
CRL Distribution Points	c = no; CRL HTTP URL = http://crl.quovadisglobal.com/qv_qwebg1.crl	
cabfOrganizationIdentifier	cabfOrganizationIdentifier 2.23.140.3.1	Optional Refer to: CA/Browser Forum Ballot SC17
qcStatements		
id-etsi-qcs- QcCompliance	id-etsi-qcs (1 0.4.0.1862.1.1) esi4-qcStatement-1: Claim that the certificate is an EU Qualified Certificate in accordance with Regulation EU No 910/2014	Refer to: etsi

attributes of the legal person, shall be verified using methods which provide equivalent assurance in terms of reliability to the physical presence of an authorised representative of the legal person and for which QuoVadis can prove the equivalence. This may include via physical presence, Remote Identity Verification (RIV4 only), or reliance on a Qualified Electronic Signature.

11.4. QUOVADIS QCP-W-PSD2

ETSI TS 119 495 defines QWAC profiles and TSP policy requirements under the Payment Services Directive (EU) 2015/2366, which are supplemented by Ballot SC17 of the CA/Browser Forum.

QuoVadis QCP-w-psd2 follow the same profile as QuoVadis QEVCP-w Certificates with the following variations:

Field	Value	Comments
Subject Distinguished Name		
Organization Identifier	subject:organisationIdentifier (2.5.4.97)	PSD2 Authorisation Number Refer to: ETSI TS 119 495 5.1 CA/Browser Forum Ballot SC17
Extension	Value	
Certificate Policies	c=no; [1] Certificate Policy: Policy Identifier=0.4.0.194112.1.4 [2] Certificate Policy: Policy Identifier= 1.3.6.1.4.1.8024.0.2.100.1.2 [3] Certificate Policy: Policy Identifier= 1.3.6.1.4.1.8024.1.450 [3,1] Policy Qualifier Info: Policy Qualifier Id=CPS Qualifier: http://www.quovadisglobal.com/repository [4] Certificate Policy: Policy Identifier=2.23.140.1.1 [5] Certificate Policy: Policy Identifier=0.4.0.19495.3.1	[1] QEVCP-w policy from ETSI EN 319 411-2 [2] QuoVadis EV policy OID [3] QuoVadis Qualified (not on QSCD) policy OID [4] CAB Forum EV OID [5] PSD2 OID QCP-w-PSD2
cabfOrganizationIdentifier		
cabfOrganizationIdentifier	cabfOrganizationIdentifier 2.23.140.3.1	Refer to: CA/Browser Forum Ballot SC17
qcStatements		
id-etsi-qcs- QcCompliance	id-etsi-qcs (1 0.4.0.1862.1.1) esi4-qcStatement-1: Claim that the certificate is an EU Qualified	Refer to:

Certificate in accordance with
Regulation EU No 910/2014

Note: PSP identifiers MAY contain hyphens, but National Registration Schemes, ISO 3166 country codes, and NCA identifiers do not. Therefore if more than one hyphen appears in the final PSP identifier, the leftmost hyphen is a separator and the remaining hyphens are part of the PSP identifier.

PSD2 Roles

The NCA can assign one or more roles (RolesOfPSP) to payment service providers. QuoVadis also confirms the PSD2 role of the Certificate Applicant (RolesOfPSP):

i) account servicing (PSP_AS)
   - OID: id-psd2-role-psp-as { 0.4.0.19495.1.1 }
     Role: PSP_AS

ii) payment initiation (PSP_PI)
   - OID: id-psd2-role-psp-pi { 0.4.0.19495.1.2 }
     Role: PSP_PI

iii) account information (PSP_AI)
   - OID: id-psd2-role-psp-ai { 0.4.0.19495.1.3 }
     Role: PSP_AI

iv) issuing of card-based payment instruments (PSP_IC)
   - OID: id-psd2-role-psp-ic { 0.4.0.19495.1.4 }
     Role: PSP_IC

Revocation Requests

Based on an authenticated request from an NCA, in accordance with ETSI TS 119 495 Section 6.2.6, QuoVadis shall revoke a PSD2 certificate within 24 hours if:

- the Authorisation of the PSP has been revoked;
- any PSP role included in the certificate has been revoked.

QuoVadis will investigate unauthenticated requests from an NCA and shall revoke the affected certificate(s) if necessary. Unauthenticated NCA notifications need not be processed within 24 hours.

11.5. CODE SIGNING

Field	Value	Comments
Version	V3	
Serial Number	Unique system generated random number assigned to each certificate, containing at least 64 bits of output.	
Issuer Signature Algorithm	sha256RSA (1.2.840.113549.1.1.11)	
Issuer Distinguished Name	CN = QuoVadis Code Signing CA G1 O = QuoVadis Limited C = BM	
Validity Period	1, 2, or 3 years expressed in UTC format	
Subject Distinguished Name		
Organisation Name	subject:organisationName (2.5.4.10)	Required field. The Subject's verified legal name.
Organisation Unit	subject:organisationUnit (2.5.6.5)	Optional field. Must not include a name, DBA, tradename, trademark, address, location, or other text that refers to a specific natural person or Legal Entity unless QuoVadis has verified this information
Common Name	subject:commonName (2.5.4.3)	Required field. The Subject's verified legal name.
State or province (if any)	subject:stateOrProvinceName (2.5.4.8)	Required if the subject:localityName field is absent. Optional if the subject:localityName fields is present.
Locality	subject:locality (2.5.4.6)	Required if the subject:stateOrProvinceName field is absent. Optional if the subject:stateOrProvinceName field is present.
Country	subject:countryName (2.5.4.6)	Required field.
Subject Public Key Information	2048-bit RSA key modulus, rsaEncryption (1.2.840.113549.1.1.1)	Increase to3072-bit June 1, 2021.
Signature Algorithm	sha256igna1353549.1.1.11)	
Extsion	Value	

Certificate Policies	c=no; Certificate Policies; {1.3.6.1.4.1.8024.0.2.200.1.1 } Certificate Policies; { 2.23.140.1.4.1 } [1,1] Policy Qualifier Info: Policy Identifier Id=CPS Qualifier: http://www.quovadisglobal.com/repository	1.3.6.1.4.1.8024.0.2.200.1.1 is the QuoVadis Code Signing OID. 2.23.140.1.4.1 is the Code Signing BaselineRequirements OID.
Authority Information Access	c=no; Access Method=Id-ad-ocsp (On-line Certificate Status Protocol - 1.3.6.1.5.5.7.48.1); URL =http://ocsp.quovadisglobal.com - id-ad-caIssuers (Certification Authority Issuer - 1.3.6.1.5.5.7.48.2); URL = http://trust.quovadisglobal.com/qvcscag1.crt	
CRL Distribution Points	c = no; CRL HTTP URL =http:// crl.quovadisglobal.com/qvcscag1.crl	

Purposes of Code Signing

The primary purpose of QuoVadis Code Signing Certificates is to establish that executable code originates from a source identified by QuoVadis. QuoVadis Certificates focus only on the identity of the Subject named in the Certificate, and not on the behaviour of the Subject. As such, Certificates are not intended to provide any assurances, or otherwise represent or warrant:

- That the Subject named in the Certificate is actively engaged in doing business;
- That the Subject named in the Certificate complies with applicable laws;
- That the Subject named in the Certificate is trustworthy, honest, or reputable in its business dealings; or
- That it is “safe” to do business with the Subject named in the Certificate.

Eligible Applicants

QuoVadis only issues Code Signing Certificates to Organisational Applicants and does not issue such certificates to Individual Applicants.

An Individual Applicant is an Applicant that is an individual and requests a Certificate that will list the Applicant’s legalname as the Certificate subject.

An Organisational Applicant is an Applicant that requests a Certificate subject other than the name of an indi thpliamed in the inme6.7 (4( )Tj E8 (t)-5.4 (t))7.8 (p)7.8 (lat.7 (a)-7 (-3.2(li)6.2.8 n)i)6.95 >>BD legs an i.9 (c)1.22(v)4

11.6. IGTF GRID CERTIFICATES

All Grid Certificates will be issued to Applicants based on cryptographic data generated by the Applicant, or based on cryptographic data that can be held only by the Applicant on a secure hardware token. Any single subject Distinguished Name must be linked to one and only one entity and must not be linked to any other entity over the lifetime of the CA.

Organization Name	subject:organisationName (2.5.4.10)
Organisation Unit	subject:organisationunitName (2.5.4.10)
Common Name	subject:commonName (2.5.4.3) cn = givenName +surName
Locality (if any)	subject:locality (2.5.4.6)
State or province (if any)	subject:stateOrProvinceName (2.5.4.8)
Country	subject:countryName (2.5.4.6)
Subject Public Key Information	2048-bit RSA key modulus, rsaEncryption (1.2.840.113549.1.1.1)
Signature Algorithm	sha256RSA (1.2.840.113549.1.1.11)
Domain Components (DC)	DC=com, DC=quovadisglobal, DC=grid, DC=<organisation identifier>, DC=hosts
Extension	Value
Authority Key Identifier	c=no; Octet String – Same as Issuer's Subject Key Identifier
Subject Key Identifier	c=no; Octet String

Organization Name	subject:organisationName (2.5.4.10)
Organisation Unit	Not permitted.
Common Name	subject:commonName (2.5.4.3) cn = Common name
Locality (if any)	subject:locality (2.5.4.6)
State or province (if any)	subject:stateOrProvinceName (2.5.4.8)
Country	subject:countryName (2.5.4.6)