QuoVadis Root CA 1G3

G3

QuoVadis PMA	3 August, 2021	4.34	Minor editorial changes, update to OCSP response.
QuoVadis PMA	24 September, 2021	4.35	Minor clareoV8teiono of0.8 ( )]12.(r)3.4 (e)-7 (v-3.(o

4.6.5. Conduct Constituting Acceptance Of A Renewal Certificate 23
4.6.6. Publication of the Renewal Certificate By The CA 23
4.6.7. Notification of Certificate Issuance By The CA To Other Entities 23
4.7. Certificate Re-Key 23
4.7.1. Circumstance For Certificate Re-Key 24
4.7.2. Who May Request Re-Key 24
4.7.3. Processing Certificate Re-Key Request 24
4.7.4. Notification Of Certificate Re-Key To Subscriber 24
4.7.5. Conduct Constituting Acceptance Of A Re-Key Certificate 24
4.7.6. Publication Of The Re-Key Certificate By The CA 24
4.7.7. Notification Of Certificate Re-Key By The CA To Other Entities 24
4.8. Certificate Modification 24
4.8.1. Circumstances For Certificate Modification 24
4.8.2. Who May Request Certificate Modification 24
4.8.3. Processing Certificate Modification Requests 24
4.8.4. Notification of Certificate Modification To Subscriber 25
4.8.5. Conduct Constituting Acceptance Of A Modified Certificate 25
4.8.6. Publication of the Modified Certificate By The CA 25
4.8.7. Notification of Certificate Modification By The CA To Other Entities 25
4.9. Certificate Revocation And Suspension 25
4.9.1. Circumstances For Revocation 25
4.9.2. Who Can Request Revocation 27
4.9.3. Procedure For Revocation Request 28
4.9.4. Revocation Request Grace Period 28
4.9.5. Time Within Which The CA Must Process The Revocation Request 28
4.9.6. Revocation Checking Requirement For Relying Parties 29
4.9.7. CRL Issuance Frequency 29
4.9.8. Maximum Latency For CRL 29
4.9.9. On-Line Revocation/Status Checking Availability 30
4.9.10. OCSP Checking Requirement 30
4.9.11. Other Forms Of Revocation Advertisements Available 30
4.9.12.

6.2.11. Cryptographic Module Rating 46
6.3. Other Aspects Of Key Pair Management 46
6.3.1. Public Key Archival 46
6.3.2. Certificate Operational Periods And Key Pair Usage Periods 46
6.4. Activation Data 47
6.4.1. Activation Data Generation And Installation 47
6.4.2. Activation Data Protection 47
6.4.3. Other Aspects Of Activation Data 47
6.5. Computer Security Controls 47
6.5.1. Specific Computer Security Technical Requirements 47
6.5.2. Computer Security Rating 48
6.6. Life Cycle Technical Controls 48
6.6.1. System Development Controls 48
6.6.2. Security M[redacted]ement Con[redacted] 49
6.6.3. Life Cycle [redacted]rity Control[redacted] 49
6.7. Network Security Controls 49
6.8. Time-Stamping 49
7. CERTIFICATE, CRL, AND OCSP PROFILES 49
7.1.

txt[redacted]

10.1.2. Key Usage And Escrow 73
10.2. QV Standard 74
10.3. QV Advanced 75
10.4. QV Advanced + ... 76
10.4.1. Swiss Regulated Certificate issued to a Natural Person 77
10.4.2. Swiss Regulated Certificate issued to a Legal Person (Company Seal) 78
10.5. QV Qualified - eIDAS 80
10.5.1. eIDAS Qualified Certificate issued to a Natural Person on a QSCD 80
10.5.2. eIDAS Qualified Certificate issued to a Natural Person 82
10.5.3. eIDAS Qualified Certificate issued to a Legal Person on a QSCD 84
10.5.4. eIDAS Qualified Certificate issued to a Legal Person 86
10.6. QV Swiss Qualified 89
10.7. QV Closed Community 90
10.7.1. Grid Certificates 91
10.8. QuoVadis Device 93
11. APPENDIX B 94
11.1. Business SSL 94
11.2. Code Signing 96

1. INTRODUCTION

1.1. OVERVIEW

This Certificate Policy/Certification Practice Statement (CP/CPS) sets out the certification processes that the QuoVadis PKI uses in the generation, issue, use, and management of Certificates and serves to notify Subscribers and Relying Parties of their roles and responsibilities concerning Certificates. This CP/CPS applies to the following Root CAs:

- QuoVadis an•Ae s R]TJ G (s-3.30 Tc 0 Tw 1.32572 d ( )Tj EMC /H2 << <</MCID 6 >>B10C -12.5783.55475

	When trust service components are provided by another party QuoVadis maintains overall responsibility and undertakes procedures to ensure that the security and functionality of the trust service meet the appropriate requirements.

1.2. DOCUMENT NAME, IDENTIFICATION AND APPLICABILITY

The Object Identifier (OID) assigned to QuoVadis is 1.3.6.1.4.1.8024. This CP/CPS applies to all CAs and Subscriber Certificates that are signed by the following

services are shared between QuoVadis and Belgian Mobile ID. QuoVadis retains overall

contracted with QuoVadis for the Certificate's issuance, or the individual responsible for requesting and a Certificate on a trusted system. Prior to verification of identity and issuance of a Certificate, a Subscriber is an . Within the QuoVadis Portal a Subscriber may also be referred to as .

Subscribers are required to act in accordance with this CP/CPS and Subscriber Agreement also Section 9.6.3.

1.3.4. Relying Parties

Relying Parties are entities that act in Reasonable Reliance on a Certificate and/or Digital Signature issued by QuoVadis. A Relying Party may, or may not, also be a Subscriber of the QuoVadis PKI. Relying parties must check the appropriate CRL or OCSP response prior to relying on information featured in a Certificate. The location of the Certificate Status service is detailed within the Certificate.

Relying Parties are required to act in accordance with this CP/CPS and the Relying Party Agreement also Section 9.6.4.

1.3.5. Other Participants

Other Participants in the QuoVadis PKI are required to act in accordance with this CP/CPS and/or applicable agreements. Other participants include Accreditation Authorities such as Policy Management Authorities, Application Software Vendors, and applicable Community-of-Interest sponsors. Accreditation Authorities are granted an unlimited right to re-distribute QuoVadis CA Certificates and related information in connection with the accreditation.

1.4. CERTIFICATE USAGE

At all times, participants in the QuoVadis PKI are required to utilise Certificates in accordance with this QuoVadis CP/CPS and all applicable laws and regulations.

1.4.1. Appropriate Certificate Uses

Certificates issued pursuant to this CP/CPS may be used for all legal authentication, encryption, access Ctio ite1.1 T7.9c(083s)-ri 01

1.5. POLICY ADMINISTRATION

1.5.1. Organisation Administering The CP/CPS

This CP/CPS and related agreements and security policy documents referenced within this document are administered by the QuoVadis Policy Management Authority (PMA).

1.5.2. Contact Person

Enquiries or other communications about this CP/CPS should be addressed to the QuoVadis PMA, DigiCert Bermuda Limited, 11 Bermudiana Road, Suite 1640, Hamilton HM-08, Bermuda

Website: https://www.quovadisglobal.com
Electronic mail: compliance@quovadisglobal.com
Customer complaints: qvcomplaints@digicert.com

1.5.2.1. Revocation Reporting Contact Person

eIDAS Regulation or eIDAS means Regulation (EU) No. 910/2014 on electronic identification and trust services for electronic transactions in the internal market.

Key Pair means two related Keys, one being a Private Key and the other a Public Key having the ability whereby one of the pair will decrypt the other.

Mailbox Address means an Email Address as specified in Section 4.1.2 of RFC 5321 and amended by Section 3.2 of RFC 6532, with no additional padding or structure.

National Competent Authority (NCA) means a national authority responsible for the regulation of payment services. The NCA approves or rejects authorisations for Payment Service Providers in its country.

Personal Name means a name of an Individual Subject. The Personal Name may be in a format preferred by the Subject, the CA, or Enterprise RA and as long as it remains a meaningful representation of the Subject's verified name.

Policy Management Authority (PMA) means the QuoVadis body responsible for overseeing and approving CP/CPS amendments and general management.

Private Key means the key of a Key Pair that is kept secret by the holder of the Key Pair, and that is used to create digital signatures and/or to decrypt electronic records or files that were encrypted with the corresponding Public Key.

Public Key means the key of a Key Pair that may be pu

Subscriber means a Holder of a Certificate chained to the QuoVadis Root Certificate, including without limitation, organisations, individuals and/or hardware and/or software devices. A Subscriber is (i) named in a Certificate or responsible for the Device named in a Certificate and (ii) holds a Private Key corresponding to the Public Key listed in that Certificate. For clarity, Subscribers are sometimes referred to as Certificate Holders.

Terms and Conditions means the Master Services Agreement, Certificate Terms of Use, Privacy Policy and relevant QuoVadis CP/CPS. The Master Services Agreement references and makes the Certificate Terms of Use, Privacy Policy and relevant QuoVadis CP/CPS part of the Terms and Conditions. The itsme Issuing CA provides its own Terms and Conditions.

1.6.2. Acronyms

ADN	Authorisation Doman Name
CA	Certification Authority or Certificate Authority
CAA	Certificate Authority Authorisation
CP/CPS	Certificate Policy & Certification Practice Statement
CRL	Certificate Revocation List
CSR	Certificate Signing Request
CT	Certificate Transparency
eIDAS	Regulation (EU) 910/2014
ERA	Enterprise Registration Authority
ETSI	European Telecommunications Standards Initiative
EUTL	EU Trusted List
EV	Extended Validation
FIPS	Federal Information Processing Standard
FQDN	Fully Qualified Domain Name
ICANN	Internet Corporation for Assigned Names and Numbers
IETF	Internet Engineering Task Force
IGTF	International Grid Trust Federation
ITU	International Telecommunication Union
OID	Object Identifier
OCSP	Online Certificate Status Protocol
PKCS	Public Key Cryptography Standard
PKI	Public Key Infrastructure
PKIX	IETF Working Group on Public Key Infrastructure
PMA	QuoVadis Policy Management Authority
Portal	Certificate Management System
PSP	Payment Service Provider
QSCD	Qualified Electronic Signature/Seal Creation Device
RA	Registration Authority
S/MIME	Secure MIME (Multipurpose Internet Mail Extensions)

SSL	Secure Sockets Layer
SSCD	Signature/Seal Creation Device
TLS	Transaction Layer Security
UTC	Coordinated Universal Time
X.509	The ITU-T standard for Certificates and their corresponding authentication framework

1.6.3. References

This CP/CPS describes the practices used to comply with the current versions of the following policies, standards, and requirements as relevant

Standards / Law	
WebTrust	WebTrust Principles and Criteria for Certification Authorities

Standards / Law
ETSI EN 319 422

QuoVadis for the Subject of the Certificate, or an identifier selected by an Enterprise RA which uniquely identifies the Subject of the Certificate within the organization.

3.1.4. Rules For Interpreting Various Name Forms

Distinguished Names in Certificates are interpreted using X.500 standards and ASN.1 syntax. QuoVadis may allow the conversion of Identity information usually rendered in non-ASCII characters (for example é and à may be represented by e or a, and umlauts such as ö or ü may be represented by oe or ue, o or u respectively). QuoVadis may use language variants (such as Munich or München) for geographic names. For Personal Names, QuoVadis include an ASCII character name that is not a direct Conversion of the Applicant's registered name provided that it is verified in a Reliable Data Source or suitable Attestation.

3.1.5. Uniqueness Of Names

The Subject Name of each Certificate issued by an Issuing CA shall be unique within each class of Certificate issued by that Issuing CA over the lifetime of that Issuing CA and shall conform to applicable X.500 standards for the uniqueness of names.

The Issuing CA may, if necessary, insert additional numbers or letters to the Subscriber's Subject Common Name, or other attribute such as Subject serialNumber, in order to distinguish between two Certificates that would otherwise have the same Subject Name. Name uniqueness is not violated when multiple Certificates are issued to the same entity.

3.1.6. Recognition, Authentication , And Role Of Trademarks

3.2. UNLESS OTHERWISE SPECIFICALLY STATED IN THIS CP/CPS, QUOVADIS DOES NOT VERIFY AN APPLICANT'S RIGHT TO USE A TRADEMARK AND DOES NOT RESOLVE TRADEMARK DISPUTES. QUOVADIS MAY REJECT ANY APPLICATION OR REQUIRE REVOCATION OF ANY CERTIFICATE THAT IS PART OF A TRADEMARK DISPUTE.INITIAL IDENTITY VALIDATION

QuoVadis may use any legal means of communication or investigation to ascertain the identity of an organisational or individual Applicant in compliance with this CP/CPS. QuoVadis may refuse to issue a Certificate in its sole discretion.

3.2.1. Method To Prove Possession Of Private Key

Issuing CAs shall establish that each Applicant for a Certificate is in possession and control of the Private Key corresponding to the Public Key contained in the request for a Certificate. The Issuing CA shall do so in accordance with an appropriate secure protocol, such as the IETF PKIX Certificate Management Protocol, including PKCS#10. This requirement does not apply where a Key Pair is generated on behalf of a Subscriber

3.2.2. Authentication Of Organisation Identity

The Identity of an Organisation (legal person) is required to be authenticated with respect to each Certificate that asserts (i) the identity of an Organisation; or (ii) an Individual, system, device, or other organisational entity's affiliation with an Organisation. Without limitation

iv) Communicating with the Domain's administrator using a constructed email address created by pre-pending 'admin', 'administrator', 'webmaster', 'hostmaster', or 'postmaster' to the Authorisation Domain Name (ADN). Performed in accordance with TLSBR Section 3.2.2.4.4;

v) TLSBR Section 3.2.2.4.5 is no longer used because it is deprecated as of August 1, 2018;

vi) TLSBR Section 3.2.2.4.6 is no longer used because it is deprecated as of April 24, 2020

vii) Confirming the Applicant's control over the requested ADN (which may be prefixed with a label that begins with an underscore character) by confirming the presence of a agreed-upon Random Value in a DNS record. Performed in accordance with TLSBR Section 3.2.2.4.7;

viii) Confirming the Applicant's control over the FQDN through control of an IP address returned from a DNS lookup for A or AAAA records for the FQDN, performed in accordance with (me)5tb3.4 ((da)-7 i/.6 (L)-7.1 (S)]T

3.2.2.5. Verification of Country

If the Applicant requests a publicly-trusted TLS Certificate that will contain the countryName field and other Subject Identity Information, then QuoVadis verifies the identity of the Applicant, and the authenticity of the Applicant Representative's Certificate Request using a verification process meeting the requirements of Section 3.2.2.1 in the TLS BR and this Section. QuoVadis inspects any document relied upon for alteration or falsification.

3.2.3. Authenticationticap-0.002 Tw 0.ap-03 0 Td [(A)7 (u)2-3.2thea .2.5 0.n

proofing. If digital identity documents are used as evidence, only eMRTDs (Electronic Machine Readable Travel Documents) according to ICAO 9303 part 10 and other digital documents that offer comparable reliability of the identity shall be accepted.

The Trusted Registers and identity documents (such as passports and national identity cards accepted in QuoVadis verification procedures are identified in
in the QuoVadis Repository.

Identity proofing may use additional digital or physical identity documents, Trusted Registers, proof of access or other documents and Attestations as supplementary evidence. Only official national or nationally approved registers are accepted as Trusted Registers.

By loading or using identity proofing software provided by QuoVadis, Applicants agree that such use will be subject to the terms and conditions of the Master Services Agreement. Use of the software may also be subject to additional terms between the Applicant and the identity proofing software provider.

3.2.3.1. Physical Presence

In-person (manual) verification requires the physical presence of the Applicant in order to conduct the identity proofing, to validate the identity document, and to bind the identity to the Applicant. The Applicant is not required to be present for all steps of the verification, which may include manual procedures, the use of automated procedures (including identity proofing software), or a hybrid approach using manual and automated procedures.

Entities that can perform this verification include the CA or RA, a Public Official or third-party validator approved by QuoVadis, or a registered Notary. In some cases, a delegated RA such as an Enterprise RA may confirm attributes where Certificates may assert the Individual's affiliation with an Organisation or rely upon previously conducted procedures, accepted Know Your Customer (KYC) standards, or a contractual relationship with the RA.

3.2.3.2. Remote Identity Verification

Remote Identity Verification allows the Applicant to use identity proofing m

Last name	ID valid until	Issuing authority

- A formal contract must be entered into with QuoVadis, which includes a ‘right to audit’ clause; and
- The CA must operate under a CPS that meets QuoVadis requirements.

3.3. IDENTIFICATION AND AUTHENTICATION FOR RE-KEY REQUESTS

3.3.1. Identification and Authentication For Routine Re-Key

Subscribers may request re-key of a Certificate prior to a Certificate’s expiration. After receiving a request for re-key, QuoVadis creates a new Certificate with the same Certificate contents except for a new Public Key and, optionally, an extended validity period. If the Certificate has an extended validity period, QuoVadis may perform some revalidation of the Applicant but may also rely on information previously provided or obtained. QuoVadis does not re-key a Certificate without additional Identification and Authentication if doing so would allow the Subscriber to use the Certificate beyond the limits specified for the applicable Certificate Profile.

3.3.2. Identification and Authentication For Re-Key After Revocation

QuoVadis does not allow re-key after revocation. To re-key a revoked Certificate, the Subscriber must undergo the initial Identification and Authentication process.

3.4. IDENTIFICATION AND AUTHENTICATION FOR REVOCATION REQUESTS

All revocation requests are authenticated by QuoVadis or the RA responsible for issuing the Certificate. QuoVadis authenticate revocation requests by referencing the Certificate’s Public Key, regardless of whether the associated Private Key is compromised. A Subscriber may request that their Certificate be revoked by:

- Authenticating to a QuoVadis Portal and requesting revocation via that system;
- Applying in person to the RA, Issuing CA or QuoVadis supplying either original proof of identification in the form of a valid Passport or National ID;
- Telephonic commun(o)6.9 (r)10.3 (7 (u)-3.2A0 T 6-3.2 0 T[(th)( )Tj 0.006 Tc 5)l p at

4.1.2. Enrolment Process And Responsibilities

Certificate Requests must be in a form prescribed by the Issuing CA and typically include i) an application form including all registration information as described by this CP/CPS, ii) secure generation of KeyPair and delivery of the Public Key to QuoVadis (a CSR may not be required), iii) acceptance of the relevant Subscriber Agreement or other terms of use upon which the Certificate is to be issued, and iv) payment of fees. All applications are subject to review, approval, and acceptance by the Issuing CA in its discretion.

A Certificate R

QuoVadis documents potential issuances that were prevented by a CAA record, and may not dispatch reports of such issu-7.1 (is)-4.8 (s)-4.7 (u)-.7 (ts)i8 (uq.7 4.8 (u)-3.2 (e)-7 (s)-8.7 (ts)- (u)toot)-13.2 ( )-11.9(th)-3.24.7 (u) (c)-5.8 (n

Ao1(0 3 (4 (r) 3 e (e)-7 (t (8)-7 (t)]TJ 1 T002 T)-171173 0 Td ()T0132973

4.4. CERTIFICATE ACCEPTANCE

4.4.1. Conduct Constitutin g Certificate Acceptance

The Certificate Requester is responsible for installing the issued Certificate on the Subscriber computer or cryptographic module according to the Subscriber's system specifications. A Subscriber

iii) the Certificate is being used for its intended purposes and in accordance with this CP/CPS.

4.6. CERTIFICATE RENEWAL

4.6.1. Circumstance For Certificate Renewal

Renewal means the issuance of a new Certificate to the Subscriber without changing the Subscriber or other participant's Public Key or any other information in the Certificate. QuoVadis may renew a Certificate if:

i) the associated Public Key has not reached the end of its validity period;

ii) the Subscriber and attributes are consistent; and

iii) the associated Private Key remains uncompromised.

QuoVadis may also renew a Certificate if a CA Certificate is rekeyed or as otherwise necessary to provide services to a customer. QuoVadis may notify Subscribers prior to a Certificate's expiration date. QuoVadis renewal requires payment of additional fees. QuoVadis may renew a certificate after expiration if the relevant industry permits such practices.

4.6.2. Who May Request Renewal

Only the Certificate Subject or an authorised representative of the Certificate Subject may request renewal of the Subscriber's Certificates.

4.6.3. Processing Certificate Renewal Requests

Renewal application requirements and procedures are generally the same as those used during the Certificate's original issuance, but QuoVadis may use previously collected information that is still considered fresh under applicable industry standards. QuoVadis will revalidate any information that is older than the periods specified in applicable standards for the Certificate Policy. QuoVadis may refuse to renew a Certificate if it cannot verify any rechecked information.

4.6.4. Notification Of New Certificate Issuance To Subscriber

QuoVadis may deliver the Certificate in any secure fashion, such as using a QuoVadis Portal.

4.6.5. Conduct Constituting Acceptance Of A Renewal Certificate

Conduct constituting acceptance of a renewed Certificate is in accordance with Section 4.4.1. Issued Certificates are considered accepted 30 days after the Certificate is renewed, or earlier upon use of the Certificate when evidence exists that the Subscriber used the Certificate.

4.6.6. Publication of the Renewal Certificate By The CA

QuoVadis publishes a renewed Certificate by delivering it to the Subscriber. All renewed CA Certificates are published in QuoVadis Repository.

4.6.7. Notification of Certificate Issuance By The CA To Other Entities

v) The technical content or format of the Certificate presents an unacceptable risk to application software vendors, Relying Parties, or others;

vi) The Subscriber was added as a denied party or prohibited person to a blocklist or is operating from a destination prohibited under the laws of the United States;

vii) For Adobe Signing Certificates, Adobe has requested revocation; or

viii) For code-signing Certificates, the Certificate was used to sign, publish, or distribute malware, code that is downloaded without user consent, or other harmful content.

ix) QuoVadis receives notice or otherwise becomes aware that there has been some other modification of the information pertaining to the Subscriber that is contained within the Certificate;

x) The Subscriber fails or refuses to comply, or to promptly correct inaccurate, false or misleading information after being made aware of such inaccuracy, misrepresentation or falsity;

QuoVadis always revokes a Certificate if the binding between the Subje9 (f)0.8 (a)-nn (ay)4 0 (a)-6.9 tio wa Qasoe

Within 24 hours after receiving a Certificate problem report or revocation request, QuoVadis investigates the facts and circumstances involved with the report and will provide a preliminary report on its findings to both the Subscriber and the entity who filed the Certificate problem report.

After reviewing the facts and circumstances, QuoVadis works with the Subscriber and any entity reporting the Certificate problem report or other revocation-related notice to establish whether or not the Certificate will be revoked, and if so, a date which QuoVadis will revoke the Certificate. The period from receipt of the Certificate problem report or revocation-related notice to published revocation must not exceed the time frame set forth in Section 4.9.1. The date selected by QuoVadis will consider the following criteria:

i) The nature of the alleged problem (scope, context, severity, magnitude, risk of harm);

ii) The consequences of revocation (direct and collateral impacts to Subscribers and Relying Parties);

iii) The number of Certificate problem reports received about a particular Certificate or Subscriber;

iv)

- SHA512WithRSAPSS
- PureEd25519

x A valid Mailbox Address so that you can receive confirmation of your problem report and associated certificate revocations

QuoVadis will select the CRLReason code "keyCompromise" (value 1) upon discovery of such reason or as required by an applicable CP/CPS. Should a CA Private Key become compromised, the CA and all Certificates issued by that CA shall be revoked. QuoVadis provides additional instructions and support for keyCompromise at https://www.quovadisglobal.com/certificate-revocation/ and other resources as indicated in Section 1.5.21 of this CP/CPS

4.9.13. Circumstances For Suspension

S.928-2 (sp)-2 (e)2 (n)5 (si)on 2 9 0 9 3 0

4.12. KEY ESCROW AND RECOVERY

QuoVadis provides optional Private Key Escrow services for certain Certificate Profiles (Appendix A, Section 10.1.2) under this CP/CPS. Private Key Escrow is only available if the Enterprise RA Administrator directs at the Account level. Private Key Escrow is prohibited for the following Certificate types:

- x CA Certificates
- x QV Advanced+ Certificates
- x QV Qualified Certificates
- x Any Certificate whose Private Key Usage is dedicated to Signing or Authentication
- x TLS Certificates
- x Codesigning Certificates

Private Key Escrow shall not be allowed when the nonRepudiation keyUsage is present in a Certificate as of version 4.32 of this CP/CPS.

4.12.1. Key Escrow And Recovery Policy And Practices

RAs are permitted to instruct QuoVadis to escrow the Subscriber's Encryption Private Key as specified in their RA Agreement. End-user Subscriber Private Keys shall only be recovered under the circumstances permitted within the RA Agreement and QuoVadis Portal administrator guide.

Escrowed Private Keys are stored in encrypted form using the QuoVadis Portal. Subscribers are notified when their Private Keys are escrowed. Properly authenticated Subscribers may subsequently retrieve their own Private Keys.

In addition, properly authenticated RA Officers with specific Key Recovery permissions may request retrieval of a Subscriber's Private Keys under the following conditions:

- RAs must protect Subscriber's escrowed Private Keys from unauthorised disclosure.
- RAs may retrieve Subscriber's escrowed Private Keys only for properly authenticated and authorised requests for recovery.
- RAs shall recover a Subscriber's escrowed Private Keys without the Subscriber's authority only for legitimate and lawful purposes, such as to comply with judicial or administrative process or a search warrant, and not for any illegal, fraudulent, or other wrongful purpose.
- RAs must revoke the Subscriber's Key Pair prior to recovering the Private Key.
- RAs may not disclose or allow to be disclosed escrowed keys or archive key-related information to any third party unless required by the law, government rule, or regulation; by the enterprise's organisation policy; or by order of a court of competent jurisdiction.
- RAs are not required to communicate any information concerning any key recovery to the Subscriber except when the Subscriber has requested recovery.

4.12.2. Session Key Encapsulation And Recovery Policy And Practices

Not applicable.

5. FACILITY, MANAGEMENT, AND OPERATIONAL CONTROLS

This Section of the CP/CPS provides a high level description of the security policy, physical and logical access control mechanisms, service levels, and personnel policies used by QuoVadis to provide trustworthy and reliable CA operations. QuoVadis maintains a security program to:

i) Protect the confidentiality, integrity, and availability of data and business process;

5.1.8. Off-Site Backup

An off-site location is used for the storage and retention of backup software and data. The off-site storage:

i) is available to authorised personnel 24x7 for the purpose of retrieving software and data; and

ii) has appropriate levels of physical security in place (i.e. software and data are stored in fire-rated safes and containers which are located behind access-controlled doors in areas accessible only by authorised personnel).

5.2. PROCEDURAL CONTROLS

Administrative processes are dealt with and described in detail in the various documents used within and supporting the QuoVadis PKI. Issuing CAs are required to ensure that administrative procedures related to personnel and procedural requirements, and physical and technological security mechanisms, are maintained in accordance with this CP/CPS and other relevant operational documents.

5.2.1. Trusted Roles

Personnel acting in trusted roles include CA, TSA, and RA system administration personnel, and personnel involved with identity vetting and the issuance and revocation of Certificates. The functions and duties performed by persons in trusted roles are distributed so that one person alone cannot circumvent security measures or subvert the security and trustworthiness of the PKI or TSA operations. A list of personnel appointed to trusted roles is maintained and reviewed annually.

5.2.1.1. CA Administrators

The CA Administrator installs and configures the CA software, including key generation, key backup, and key management. The CA Administrator performs and securely stores regular system backups of the CA system. CA Administrators do not issue Certificates to Subscribers.

5.2.1.2.

5.4. AUDIT LOGGING PROCEDURES

5.4.1. Types Of Events Recorded

QuoVadis records details of the actions taken to process a Certificate Request and to issue a Certificate, including to iTJ 0e (n)2.7 (d)-12.1DC q 72 739.32 156 16.68 re W n BT /TT0 1 Tf 9.96 -0 0 9.G (c)-5.ioe.8 (s)-4g.1 (9( )]T19

5.4.3. Retention Period For Audit Log

Audit logs relating to the Certificate lifecycle are retained as archive records for a period no less than eleven (11) years for Swiss Qualified Certificates and for seven (7) years for all other Certificates starting from the destruction of the CA Private Key or revocation or expiration of the Certificate. Certain high volume system generated logs are retained for 18 months based on a risk assessment. QuoVadis makes the audit logs available to auditors, as defined in section 8, available upon request.

5.4.4. Protection Of Audit Log

The relevant audit data collected is regularly analysed for any attempts to violate the integrity of any element of the QuoVadis PKI. Only certain QuoVadis Trusted Roles and auditors may view audit logs in whole. QuoVadis decides whether particular audit records need to be viewed by others in specific instances and makes those records available. Consolidated logs are protected from modification and destruction. All audit logs are protected in an encrypted format via a Key and/or Certificate generated especially for the purpose of protecting the logs.

5.4.5. Audit Log Backup Procedures

Each Issuing CA performs an onsite backup of the audit log daily. The backup process includes weekly
p1 Td [(pe2.3 (w)8.9 (eekly)4 lj EMC /P < (d (k)5 .1 (u)-4 (res)]TJ 0 Tc 0 Tw Tc -0.3tbh 0 Td [(o)6.9 5ep)) ia/2 (r)10.3 (m)

5.5. RECORDS ARCHIVAL

5.5.1. Types Of Records

5.5.6. Archive Collection System

The QuoVadis Archive Collection System is internal to QuoVadis provides assistance to Issuing CAs and RAs within the QuoVadis PKI to preserve their audit trails.

5.5.7. Procedures To Obtain And Verify Archive Information

Access to archives is granted only to persons in Trusted Roles and based on least privilege. The contents of the archives will not be released as a whole, except as required by law. QuoVadis may decide to release records of individual transactions upon request of any of the entities involved in the transaction or their authorised representatives. A reasonable handling fee per record (subject to a minimum fee) will be assessed to cover the cost of record retrieval.

5.6. KEY CHANGEOVER

Key changeover is not automatic, but procedures enable the smooth transition from expiring CA Certificates to new CA Certificates. Towards the end of the CA Private Key's lifetime, QuoVadis ceases using its expiring CA Private Key to sign Certificates (well in advance of expiration) and uses the old Private Key only to sign CRLs and OCSP responder Certificates associated with that key. A new CA signing Key Pair is commissioned and all subsequently issued Certificates and CRLs are signed with the new private signing key. Both the old and the new Key Pairs may be concurrently active.

5.7. COMPROMISE AND DISASTER RECOVERY

5.7.1.

QuoVadis may generate a new Key Pair and sign a new Certificate. If a disaster physically damages QuoVadis' equipment and destroys all copies of QuoVadis' Private Keys, then QuoVadis will provide notice to affected parties at the earliest feasible time.

5.7.4. Business Continuity Capabilities A fter a Disaster

To maintain the integrity of its services, QuoVadis implements data backup and recovery procedures as part of its Business Continuity Management Plan (BCMP). Stated goals of the BCMP are to ensure that certificate status services be only minimally affected by any disaster involving QuoVadis' primary facility and that QuoVadis be capable of maintaining other services or resuming them as quickly as possible following a disaster. QuoVadis periodically reviews, tests, and updates the BCMP and supporting procedures.

5.8. -8 (8.)]TJ0 Tc 0 Tw6.49 0 Td181

Level 3 and/or Common Criteria EAL 4 or higher. Hardware Security Modules (HSM) are always stored in a physically secure environment and are subject to security controls throughout their lifecycle. Activation of the hardware requires the use of two-factor authentication tokens. QuoVadis creates auditable evidence during the key generation process to prove that the CP/CPS was followed and role separation was enforced during the key generation process. QuoVadis requires that an external auditor witness the generation of or review a recording of any CA keys to be used as publicly-trusted Root Certificates. For other CA Key Pair generation ceremonies, an Internal Auditor, external auditor, or independent third party attends the ceremony, or an external auditor examines the signed and documented record of the key generation ceremony, as allowed by applicable policy.

- using a cryp

Subscribers are solely responsible for protecting their Private Keys in a manner commensurate with the Certificate Profile. Subscribers should use a strong password or equivalent authentication method to prevent unauthorized access or use of the Subscriber's Private Key. Subscribers shall, when deactivated, Private Keys shall be kept in encrypted form only and secured. At a minimum, Subscribers are required to authenticate themselves to the cryptographic module before activating their Private Keys.

6.2.9. Method Of Deactivating Private Key

QuoVadis' Private Keys are deactivated via manual and passive logout procedures on the applicable HSM device when not in use. QuoVadis never leaves its HSM devices in an active unlocked or unattended state.

Subscribers should deactivate their Private Keys via logout and removal procedures when not in use.

Type

6.6.2. Security Management Controls

QuoVadis has mechanisms in place to control and continuously monitor the security-related configurations of its CA systems. When loading software onto a CA system, QuoVadis verifies that the software is the correct version and is supplied by the vendor free of any modifications.

6.6.3. Life Cycle Security Controls

No stipulation.

6.7. NETWORK SECURITY CONTROLS

QuoVadis CA and RA functions are performed u0.8 25i1igeo9 -1.2 (o)-3.1 k(e)--3.1 (s7-4.8 (s7-4.8 (e9-6.9 (c8)0.8 (u0.8 2 (re

7.1.1. Version Number(s)

All Certificates are X.509 version 3 Certificates.

7.1.2. Certificate Extensions

The extensions defined for X.509 v3 Certificates provide methods for associating additional attributes with users or Public Keys and for managing relationships between CAs. Appendix A and Appendix B.

Root CA, Subordinate CA, and Subscriber Certificates abide by Section 7.1.2 of the TLS BR or S/MIME BR as applicable, and configure th(on)2.8 (f)-1 he 7-6.9 (th)-15.2 ((o8-5 (x)221 0 (s)m ( )a1.6 (h)-3.2 (a)-6.9 (r)3.3(h)-3.2 (ea.7 (

7.1.5.2. Name-Constrained emailProtection CAs

- QuoVadis is made aware of a demonstrated or proven method that can easily compute the Subscriber's Private Key based on the Public Key in the Certificate (such as a Debian weak key, see https://wiki.debian.org/TLSkeys); or
- the Subscriber requests that QuoVadis revoke the Certificate for this reason, with the scope of revocation being described below.

If anyone requesting revocation for keyCompromise has previously demonstrated or can currently demonstrate possession of the Private Key of the Certificate, then QuoVadis will revoke all instances of that key across all Subscribers.

If the Subscriberrequests that QuoVadis revoke the Certificate ions fi.9 (p)0.8 (osd009 Tw [(P)7.8 d [(u)3.8)6.9.2 10 3 2. (e K)8

between the domain name registrant and the Applicant has terminated, or the domain name registrant has failed to renew the domain name).

Unless keyCompromise is being used, cessationOfOperation must be used when:

- the Subscriber has requested that their Certificate be revoked for this reason; or
- QuoVadis received verifiable evidence that the Subscriber no longer controls, or is no longer authorized to use, all of the domain names in the Certificate.

Otherwise, cessationOfOperation must not be used.

affiliationChanged

The CRLReason affiliationChanged is intended to be used to indicate that the Subject's name or other subject identity information in the Certificate has changed, but there is no cause to suspect that the Certificate's Private Key has been compromised.

Unless CRLReason is being used, affiliationChanged will be used when:

- the Subscriber has requested that their Certificate be revoked for this reason; or
- QuoVadis replaced the Certificate due to changes in the Certificate's subject information and the CA has not replaced the Certificate for the other reasons: keyCompromise, superseded, cessationOfOperation, or privilegeWithdrawn.

Otherwise, [illegible]

7.5. CERTIFICATE FIELDS AND ROOT CA CERTIFICATE HASHES

7.5.1. Certificate Fields

7.5.2. QuoVadis Root Certificate Hashes

Note that all QuoVadis CA Certificates and CRLs are available for download from the QuoVadis Repository at https://www.quovadisglobal.com/repository .

7.5.2.1. QuoVadis Root CA 1 G3 Certificate Hashes

Field	Certificate Profile
Serial Number	78 58 5f 2e ad 2c 19 4b e3 37 07 35 34 13 28 b5 96 d4 65 93
Signature Block	Signature matches Public Key Root Certificate: Subject matches Issuer Key Id Hash (sha1): 92 ae ef 0e 89 02 ee 6d 79 68 d1 a1 0e 75 60 01 fa e4 eb fc Subject Key Id (precomputed): a3 97 d6 f3 5e a2 10 e1 ab 45 9f 3c 17 64 3c ee 01 70 9c cc Cert Hash(sha1): 1b 8e ea 57 96 29 1a c9 39 ea b8 0a 81 1a 73 73 c0 93 79 67

7.5.2.2. QuoVadis

8.2. IDENTITY AND QUALIFICATIONS OF ASSESSOR

WebTrust auditors must meet the requirements of Section 8.2 of the TLS BR and S/MIME BR. ETSI Conformance Assessment Bodies must meet the requirements of the relevant national accrediting authority. Auditors shall be experienced in performing information security audits, specifically having significant experience with PKI and cryptographic technologies. [SSE lyw 0.217 oV (h3.4 (s)-j -0.g)-83 Tc 0.00(a)-7 NSHIP.277 0 Tc 0

8.3. ASSESSOR'S RELATIONSHIP TO ASSESSED ENTITY

The LANTL ra8-9 (T5o (og)-1 3 (e)-7 ()3.3 (mi)-12.2 2.4 (nC(og)3 .012 -1.1 (e)-7 ( )3.33 (mdn)-9.3 (p)0.)-3.2 (s)-4.8 (t a)-

9. OTHER BUSINESS AND LEGAL MATTERS

9.1. FEES

9.1.1. Certificate Issuance Or Renewal Fees

QuoVadis charges fees for verification, certificate issuance and renewal. QuoVadis may change its fees at any time in accordance with the applicable customer agreement

9.1.2. Certificate Access Fees

QuoVadis may charge a reasonable fee for access to its certificate databases

9.1.3. Revocation Or Status Information Access Fees

QuoVadis does not charge a certificate revocation fee or a fee for checking the validity status of an issued Certificate using a CRL. QuoVadis may charge a fee for providing customized CRLs, OCSP services, or other value-added revocation and status information services. QuoVadis does not permit access to revocation information, Certificate status information, or time stamping in their Repositories by third parties that provide products or services that utilize such Certificate status information without QuoVadis' prior express written consent.

9.1.4. Fees For Other Services

QuoVadis does not charge

9.4. PRIVACY OF PERSONAL INFORMATION

9.4.1. Privacy Plan

QuoVadis follows the Privacy Notices

9.5.1. Property Rights In Certificates A nd Revocation Information

QuoVadisretains all intellectual property rights in and to the Certificates and revocation information that it issues. QuoVadis and customers shall grant permission to reproduce and distribute Certificates on a nonexclusive royalty-free basis, provided that they are reproduced in full and that use of Certificates is subject to the Relying Party Agreement referenced in the Certificate. QuoVadis, and customers shall grant permission to use revocation information to perform Relying Party functions subject to the applicable CRL usage agreement, Relying Party Agreement, or any other applicable agreements.

9.5.2. Property Rights In T he CP/CPS

Issuing CAs acknowledge that QuoVadis retains all intellectual property rights in and to this CP/CPS.

9.5.3. Property Rights In Names

A Subscriber and/or Applicant retains all rights it has (if any) in any trademark, service mark, or trade name contained in any Certificate and Distinguished Name within any Certificate issued to such Subscriber or Applicant.

9.5.4. Property Rights I

QuoVadis hereby warrants (i) it has taken reasonable steps to verify that the information contained in any Certificate is accurate at the time of issue (ii) Certificates shall be revoked if QuoVadis believes or is notified that the contents of the Certificate are no longer accurate, or that the Private Key associated with a Certificate has been compromised in any way.

QuoVadis makes no other warranties, and all warranties, express or implied, statutory or otherwise, are excluded to the greatest extent permissible by applicable law, including without limitation all warranties as to merchantability or fitness for a particular purpose.

QuoVadis provides test certificates for all types of Certificates.

9.6.2. RA Representations And Warranties

RAs represent and warrant that:

i) The RA's certificate issuance and management services conform to the QuoVadis CP/CPS and applicable CA or RA Agreements,

ii) Information provided by the RA does not contain any false or misleading information,

iii) Reasonable steps are taken to verify that the information contained in any Certificate is accurate at the time of issue,

iv) Translations performed by the RA are an accurate translation of the original information,

v) All Certificates requested by the RA meet the requirements of this CP/CPS and RA Agreement, and

vi) The RA will request that Certificates be revoked by QuoVadis if they believe or are notified that the contents of the Certificate are no longer accurate, or that the key associated with a Certificate has been compromised in any way.

QuoVadis' RA Agreement may contain additional representations. Subscriber Agreements may include additional representations and warranties.

9.6.3. Subscriber Representations And Warranties

Prior to being issued and receiving a Certificate, Subscribers are solely responsible for any misrepresentations they make to third parties and for all transactions that use Subscriber's Private Key, regardless of whether such use was authorised. Subscribers are required to notify QuoVadis and any applicable RA if a change occurs that could affect the status of the Certificate.

QuoVadis requires, as part of the Subscriber Agreement or Terms of Use, that the Applicant make the commitments and warranties in this Section for the benefit of QuoVadis and all Relying Parties and Application Software Vendors. This make take the form of either:

i) The Applicant's agreement to the Subscriber Agreement with QuoVadis, or

ii) The Applicant's acknowledgement of the Terms of Use.

Subscribers represent to QuoVadis, Application Software Vendors, and Relying Parties that, for each Certificate, the Subscriber will:

i) Securely generate its Private Keys and protect its Private Keys from compromise, and exercise sole and complete control and use of its Private Keys;

ii) Provide accurate and complete information when communicating with QuoVadis, and to respond to QuoVadis' instructions concerning Key Compromise or Certificate misuse;

iii) Confirm the accuracy of the certificate data prior to installing or using the Certificate;

iv) For Qualified Certificates (a) if the policy requires the use of a QSCD, Electronic Signatures must only be created by a QSCD, (b) in the case of natural persons, the Private Keys should only be used for Electronic Signatures, and (c) in the case of legal persons, the Private Key must be maintained and used under the control of the Subscriber and it should only be used for Electronic Seals.

v) Promptly (a) request revocation of a Certificate, cease using it and its associated Private Key, and notify QuoVadis if there is any actual or suspected misuse or compromise of the Private Key associated with the Public Key included in the Certificate, and (b) request revocation of the Certificate, and cease using it, if any information in the Certificate is or becomes incorrect or inaccurate;

vi) For Remote Identity Verification, use the identity proofing software distributed by QuoVadis. The Subscriber is obliged to agree with the processing of biometric data for identity verification purposes during Remote Identity Verification;

vii) Ensure that individuals using Certificates on behalf of an organisation have received security training appropriate to the Certificate;

viii) Use the Certificate only for authorised and legal purposes, consistent with the Certificate purpose, this CP/CPS, and the relevant Subscriber Agreement, including only installing TLS Server Certificates on servers accessible at the Domain listed in the Certificate and not using code signing Certificates to sign malicious code or any code that is dow-4.a3.2 (a)-7 (t i)-7 (t i)-78 (ic)- (n)9.8 (c-4.)-3.2 (a3.2 (a)-7ic)-5.7 o1P0o

x

HEREOF WILL NOT EXCEED THE AMOUNTS PAID BY OR ON BEHALF OF SUBSCRIBER TO QUOVADIS IN THE TWELVE MONTHS PRIOR TO THE EVENT GIVING RISE TO SUCH LIABILITY, REGARDLESS OF WHETHER SUCH LIABILITY ARISES FROM CONTRACT, INDEMNIFICATION, WARRANTY, TORT (INCLUDING NEGLIGENCE), STRICT LIABILITY OR OTHERWISE, AND REGARDLESS OF WHETHER QUOVADIS HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH LOSS OR DAMAGE. NO CLAIM, REGARDLESS OF FORM, WHICH IN ANY WAY ARISES OUT OF THIS CP

Customer is Domiciled in or the Services are:	Governing Law is laws of:	Court or arbitration body with exclusive jurisdiction:
Europe, Switzerland, the United Kingdom, Russia, the Middle East or Africa	England	International Chamber of Commerce, International Court of Arbitration, with seat of arbitration in the city corresponding to the QV contracting entity listed in the Order Form. For QV CH: Zurich For QV NL: Amsterdam For QV DE: Munich For QVBE/DigiCert Europe Brussels For QV UK: London

Certificate Class	Description	Policy OID	Assurance Level	Requires token?
	Relevant to the Policy in ETSI EN 319 411-2 for: EU Qualified Certificates issued to a natural person (QCP-n-qscd), with the OID 0.4.0.194112.1.2 EU Qualified Certificates issued to a legal person (QCP-l-qscd), with the OID 0.4.0.194112.1.3	ETSI policy identifier OIDs: 0.4.0.194112.1.2 (QCP-n-qscd) 0.4.0.194112.1.3 (QCP-l-qscd)		Adobe AATL Approved
	QuoVadis Qualified Certificate not on a QSCD Relevant to the Policy in ETSI EN 319 411-2 for: EU Qualified Certificates issued to a natural person (QCP-n), with the OID 0.4.0.194112.1.0 EU Qualified Certificates issued to a legal person (QCP-l), with the OID 0.4.0.194112.1.1	QuoVadis Certificate Class OID: 1.3.6.1.4.1.8024.1.450 ETSI policy identifier OIDs: 0.4.0.194112.1.0 (QCP-n) 0.4.0.194112.1.1 (QCP-l)	High	No
	QuoVadis Qualified Certificate not on a QSCD, where the device is managed by a QTSP. Relevant to the Policy in ETSI EN 319 411-2 for: EU Qualified Certificates issued to a natural person (QCP-n), with the OID 0.4.0.194112.1.0 EU Qualified Certificates issued to a legal person (QCP-l), with the OID 0.4.0.194112.1.1	QuoVadis Certificate Class OID: 1.3.6.1.4.1.8024.1.460 ETSI policy identifier OIDs: 0.4.0.194112.1.0 (QCP-n) 0.4.0.194112.1.1 (QCP-l)	High	No
QV Closed Community	Used for reliance by members of the Issuer community only. Policies are defined in the CP/CPS of the Issuing CA.	1.3.6.1.4.1.8024.1.500	Medium	Optional
QV Device	Issued to devices, including Time-stamp Certificates	1.3.6.1.4.1.8024.1.600	Medium	Optional

10.1.2. Key Usage And Escrow

Different QuoVadis Certificate Profiles may be issued with different key usages, and be eligible for optional Key Escrow, according to the following table:

Certificate Type	Key Usage/

10.3. QV ADVANCED

Purpose
QV Advanced Certificates provide reliable verification of the Subject's identity and may be used for a broad range of applications including Digital Signatures, encryption, and authentication.
Registration Process

Validation procedures for QV Advanced Certificates are based on the Normalised Certificate Policy (NCP) described in ETSI EN 319 411-1.

Subjects may include an Individual (natural person), an Organisation (legal person), or a natural person, device, or system identified in association with an Organisation. Section 3.2.2 and 3.2.3 Identity proofing may be conducted via physical presence, Remote Identity Verification (RIV4 for NFC with RIV2 as a fallback option if

10.4. QV ADVANCED +

	2.23.140.1.5	4.1 S/MIME Individual-Legacy (optional)

id-etsi-qcs-QcCompliance (0.4.0.1862.1.1) id-etsi-qcs-1	esi4-qcStatement-1: Claim that thecertificate is an EU Qualified Certificate in accordance with Regulation EU No 910/2014	Fixed
id-etsi-qcs-QcSSCD (0.4.0.1862.1.4 id-etsi-qcs-4	esi4-qcStatement-4: The private key related to the certified public key resides on a QSCD.	Fixed
id-etsi-qcs-QcType (0.4.0.1862.1.6) id-etsi-qcs-6	esi4-qcStatement-6: Type of certificate id-etsi-qcs-QcType 1 = Certificate for electronic Signatures as defined in Regulation EU No 910/2014	Fixed
id-etsi-qcs-QcPDS (0.4.0.1862.1.5) id-etsi-qcs-5	URL= https://www.quovadisglobal.com/repository	

Attribute	Values	Comment
Subjeomm6>Tf 240.96 688.i140.485		

T

Extended Key Usage	clientAuth (optional) emailProtection documentSigning	Variable (at least one is present)
qcStatements		
id-etsi-qcs-QcCompliance (0.4.0.1862.1.1) id-etsi-qcs-1	esi4-qcStatement-1: Claim that the certificate is an EU Qualified Certificate in accordance with Regulation EU No 910/2014	Fixed
id-etsi-qcs-QcSSCD (0.4.0.1862.1.4 id-etsi-qcs-4	esi4-qcStatement-4: The private key related to the certified public key resides on a QSCD.	Fixed
id-etsi-qcs-QcType (0.4.0.1862.1.6) id-etsi-qcs-6	esi4-qcStatement-6: Type of certificate id-etsi-qcs-QcType 1 = Certificate for electronic Signatures as defined in Regulation EU No 910/2014	Fixed
id-etsi-qcs-QcPDS (0.4.0.1862.1.5) id-etsi-qcs-5	URL= https://www.quovadisglobal.com/repository Language = EN	Fixed
id-qcs-pkixQCSyntax-v2 (1.3.6.1.5.5.7.11.2)	0.4.0.194121.1.1 (optional semantics identifier OID that is included in QuoVadis Certificates)	Fixed

10.5.2. eIDAS Qualified Certificate issued to a Natural Person

Purpose

The purpose of these EU Qualified Certificates are to identify the Subscriber with a high level of assurance, for the purpose of creating Advanced Electronic Signatures meeting the qualification requirements defined by the eIDAS Regulation.

This type of QuoVadis Qualified Certificates does not use a QSCD for the protection of the private key. The content of these Certificates meet the relevant requirements of:

-

Subject	/CN (mandatory) = Natural Person (/GN+/SN or Pseudonym) /GN (mandatory if CNwithout Pseudonym) /SN (mandatory if CNwithout Pseudonym) Pseudonym (optionalif natural person) /T (optional) /O (optional) /OU (optional) / organizatu/ CNno 14 7 (n.) 10 003 7 (tru) 152 (u) 0 2 (u)fv ro Td (02 0 Td [(P)0.7 (s)(434 (n)2.8 (S)1)]e 975 c -5.Td (/)Tj -0.001 1

	Signatures as defined in Regulation EU No 910/2014	
id-etsi-qcs-QcPDS (0.4.0.1862.1.5) id-etsi-qcs-5	URL= https://www.quovadisglobal.com/repository Language = EN	Fixed
id-qcs-pkixQCSyntax-v2 (1.3.6.1.5.5.7.11.2)	0.4.0.194121.1.1 (id-etsi-qcs-semanticsId-Natural) (optional semantics identifier OID that is included in QuoVadis Certificates)	Fixed
id-etsi-qcs-QcCompliance (0.4.0.1862.1.1) id-etsi-qcs-1	esi4-qcStatement-1: Claim that the certificate is an EU Qualified Certificate in accordance with Regulation EU No 910/2014	Fixed

10.5.3. eIDAS Qualified Certificate issued to a Legal Person on a QSCD

Purpose
The purpose of these EU Qualified Certificates are to identify the Subscriber with a high level of assurance, for the purpose of creating Qualified Electronic Seals meeting the qualification requirements defined by the eIDAS Regulation. This type of QuoVadis Qualified Certificate uses a QSCD for the protection of the private key. These Certificates meet the relevant ETSI "Policy for EU qrer(r)3.6[(e)-7 (T)8.7 ((E)-78 (r)3.3 (o)-12..12 0 Td 6n)9.8sprtifes

- ii) payment initiation (PSP_PI)
  OID: id-psd2-role-psp-pi { 0.4.0.19495.1.2 }
- iii) account information (PSP_AI)
  OID: id-psd2-role-psp-ai { 0.4.0.19495.1.3 }
- iv) issuing of card-based payment instruments (PSP_IC)
  OID: id-psd2-role-psp-ic { 0.4.0.19495.1.4 }

These Certificates require a QSCD that meets the requirements laid down in Annex II of the eIDAS Regulation. The Subscriber's obligations (or respectively the obligations on the TSP managing the key on their behalf) require that the Private Key is maintained (or respectively is used) under the Subject's sole control.

Attribute	Values	Comment
Subject	/CN (mandatory) =/0 /O (optional) /OU (optional) / organizationalIdentifier (mandatory) /serialNumber (optional) /E (optional) /L (optional) /ST (optional) /C (mandatory) If serialNumber is present then it must be structured per Section 5.1.3 of ETSI EN 319 412-1: • 3 character identity type reference (e.g. PAS or IDC); • 2 character ISO 3166 country code; • hyphen-minus "-" (0x2D (ASCII), U+002D (UTF-8)); and • identifier. For PSD2: • “PSD" as 3 character legal person identity type reference; • 2 character ISO 3166 [7] country code representing the NCA country; • hyphen-minus "-" (0x2D (ASCII), U+002D (UTF-8)); and • 2-8 character NCA identifier (A-Z uppercase only, no separator) • hyphen-minus "-" (0x2D (ASCII), U+002D (UTF-8)); and • PSP identifier (authorisation number as specified by the NCA).	See definitions in Section 7.1.1 Variable
SAN	/E	Optional
Certificate Policies	1.3.6.1.4.1.8024.1.400 QV Qualified QSCD or 1.3.6.1.4.1.8024.1.410 QV Qualified QSCD on behalf of 0.4.0.194112.1.3 (QCP-l-qscd)	Fixed

For PSD2:

-

10.6. QV SWISS QUALIFIED

Purpose
QV Swiss Qualified Certificates are Qualified personal certificates according to the Swiss Federal signature law (ZertES). They are issued out of the "QuoVadis Swiss Regulated SubCA" and have the notice text "qualified certificate" in the Certificate Policies user notice. QV Swiss Qualified Certificates are used to sign documents electronically. The Digital Signature is legally equivalent to a handwritten signature.
Registration Process
QV Swiss Qualified Certificates are issued in accordance with the Zer.8 (t)T54(74 oa)D.2 (at)tIn4 ThepTWn n E